



US00D838854S

(12) **United States Design Patent**
Lumme

(10) **Patent No.:** **US D838,854 S**
(45) **Date of Patent:** **** Jan. 22, 2019**

(54) **BIOSENSOR IN A HOLDER**
(71) Applicant: **Polar Electro Oy**, Kempele (FI)
(72) Inventor: **Lauri Lumme**, Oulu (FI)
(73) Assignee: **Polar Electro Oy**, Kempele (FI)
(**) Term: **15 Years**

19/00–19/34; G04B 21/12; G04B 23/12;
G04B 37/00–37/228; G04B
47/00–47/068; G01C 17/00; G01C
21/00–21/3697; G01C 22/00–22/025;
G01C 23/00–23/005; G01C 21/16; G06F
19/3481; G06F 3/00–3/027; G01P
1/00–1/26; G01P 15/00–15/18; A63C
11/02

See application file for complete search history.

(21) Appl. No.: **29/613,932**
(22) Filed: **Aug. 15, 2017**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(30) **Foreign Application Priority Data**
Feb. 23, 2017 (EM) 003763895-0002

D739,942 S * 9/2015 Pernu D24/167
D739,943 S * 9/2015 Pernu D24/167
9,138,158 B2 * 9/2015 Okuda A61B 5/0408
9,173,596 B1 * 11/2015 Berme G06F 19/3481

(51) **LOC (11) Cl.** **24-01**
(52) **U.S. Cl.**
USPC **D24/167**; D10/30; D10/70

* cited by examiner

Primary Examiner — Antoine Duval Davis
(74) *Attorney, Agent, or Firm* — FisherBroyles, LLP

(58) **Field of Classification Search**
USPC D10/30–39, 65, 70, 78, 97, 98; D11/3;
D14/138 R, 203.5, 203.6, 341, 344;
D24/16, 168, 186
CPC A63B 24/0062; A63B 71/0686; A63B
33/002; A63B 71/0622; A63B 2207/02;
A63B 2244/20; A63B 2071/0625; A63B
2033/004; A63B 2208/03; A63B 2220/30;
A63B 2220/836; A63B 2225/50; A63B
2230/065; A63B 24/00–2024/0096; A63B
2213/00; A63B 69/0028; A63B
2071/0658–2071/0666; A63B
2220/00–2220/89; A63B 2225/02; A61B
5/0205; A61B 5/6803; A61B 5/0015;
A61B 5/02416; A61B 5/1118; A61B
5/02438; A61B 2560/0214; A61B
2503/10; A61B 5/681; A61B 5/6824;
A61B 5/6825; A61B 5/6826; G04B


(57) **CLAIM**

The ornamental design for a biosensor in a holder, as shown and described.

DESCRIPTION

FIG. 1 is a side perspective view of the biosensor in a holder; FIG. 2 is a first side view of the biosensor in a holder; FIG. 3 is a second side view of the biosensor in a holder; FIG. 4 is a first end view of the biosensor in a holder; FIG. 5 is a second end view of the biosensor in a holder; FIG. 6 is a top view of the biosensor in a holder; and, FIG. 7 is a bottom view of the biosensor in a holder.

1 Claim, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7