

US00D840358S

(12) **United States Design Patent** (10) **Patent No.:** **US D840,358 S**
Zhao et al. (45) **Date of Patent:** **** Feb. 12, 2019**

(54) **CONTROL DEVICE**

(71) Applicant: **QINGDAO BRIGHT MEDICAL
MANUFACTURING CO., LTD.,**
Qingdao, Shandong Province (CN)

(72) Inventors: **Dezheng Zhao**, Qingdao (CN);
Mengtian Yi, Qingdao (CN)

(73) Assignee: **QINGDAO BRIGHT MEDICAL
MANUFACTURING CO., LTD.,**
Qingdao (CN)

(**) Term: **15 Years**

(21) Appl. No.: **29/595,916**

(22) Filed: **Mar. 3, 2017**

(30) **Foreign Application Priority Data**

Nov. 10, 2016 (CN) 2016 3 0546026

(51) **LOC (11) Cl.** **13-03**

(52) **U.S. Cl.**
USPC **D13/168; D24/186**

(58) **Field of Classification Search**
USPC D13/168, 171; D24/133, 186, 187
CPC A61B 8/4405; A61B 8/4455; A61B 8/462;
A61N 1/37235; A61N 1/37247; H01H
9/02; H01H 9/0214; H01H 9/0235; H01H
9/0242; G08C 17/00; G08C 17/02
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D435,834 S * 1/2001 Picozza D13/168
D500,494 S * 1/2005 Borsboom D14/218
D513,233 S * 12/2005 Stauffer D13/168
D527,712 S * 9/2006 Indio da Costa D13/168
7,218,249 B2 * 5/2007 Chadha G06F 3/0236
341/22

D546,818 S * 7/2007 Gautier D14/218
D548,728 S * 8/2007 Yoshiyama D14/218
D603,351 S * 11/2009 Badarello D13/168
D612,839 S * 3/2010 Kato D14/218
D633,447 S * 3/2011 Schaal D13/168
D637,178 S * 5/2011 Chiu D14/218
8,008,628 B2 * 8/2011 Boucly A61B 6/145
250/370.09
D656,104 S * 3/2012 Cook D13/168
D667,798 S * 9/2012 Burwell D13/168
D710,014 S * 7/2014 Johnson D14/486
D726,130 S * 4/2015 Burgett D13/171
D729,748 S * 5/2015 Cook D13/168
9,180,302 B2 * 11/2015 Drees A61N 1/37282
D789,545 S * 6/2017 Pippel D24/186

(Continued)

Primary Examiner — Selina Sikder

(74) *Attorney, Agent, or Firm* — Jiwen Chen

(57) **CLAIM**

The ornamental design for the control device, as shown and described.

DESCRIPTION

FIG. 1 is a front View of a first embodiment of the control device;

FIG. 2 is a rear side View thereof;

FIG. 3 is a left side View thereof;

FIG. 4 is a right side View thereof;

FIG. 5 is a bottom View thereof; and

FIG. 6 is a top View thereof.

FIG. 7 is a front View of a second embodiment of the control device;

FIG. 8 is a rear side View thereof;

FIG. 9 is a left side View thereof;


FIG. 10 is a right side View thereof;

FIG. 11 is a bottom View thereof; and,

FIG. 12 is a top View thereof.

The broken lines are for illustrative purposes only and form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D802,542 S * 11/2017 Christensen D13/168
2008/0249591 A1 * 10/2008 Gaw A61N 1/37235
607/60
2012/0101551 A1 * 4/2012 Aghassian A61N 1/37235
607/60
2013/0060300 A1 * 3/2013 Polefko A61N 1/36017
607/46
2013/0197607 A1 * 8/2013 Wilder A61N 1/3787
607/59
2017/0065259 A1 * 3/2017 Pinch A61B 8/546

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12