



US00D841988S

(12) **United States Design Patent**
Tanaka

(10) **Patent No.:** **US D841,988 S**

(45) **Date of Patent:** **** Mar. 5, 2019**

(54) **COSMETIC APPLICATOR**

(71) Applicant: **SINWA CORPORATION**, Kanagawa (JP)

(72) Inventor: **Akihiro Tanaka**, Kanagawa (JP)

(73) Assignee: **SINWA CORPORATION**, Kanagawa (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/624,587**

(22) Filed: **Nov. 2, 2017**

(30) **Foreign Application Priority Data**

May 23, 2017 (JP) 2017-010941

(51) **LOC (11) Cl.** **04-02**

(52) **U.S. Cl.**
USPC **D4/128**

(58) **Field of Classification Search**

USPC D4/128, 129, 131, 136, 138, 108, 109,
D4/119; D32/35, 51; 15/104.5, 104.16,
15/104.2, 104.31, 104.32, 164, 165, 206;
D28/65; D7/682; 452/298, 458
CPC A46B 7/026; A46B 5/005; A46B 17/04;
A46B 2200/1046

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,898,193 A * 2/1990 Gueret A45D 40/265
132/218
D623,418 S * 9/2010 Martinez D4/128
D629,617 S * 12/2010 Yasuda D4/128
D650,992 S * 12/2011 Legassie D4/128

(Continued)

Primary Examiner — Austin Murphy

(74) *Attorney, Agent, or Firm* — Roberts Mlotkowski
Safran Cole & Calderon P.C.

(57) **CLAIM**

The ornamental design for a cosmetic applicator, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of an embodiment of the cosmetic applicator;

FIG. 2 is a top view of the cosmetic applicator shown in FIG. 1;

FIG. 3 is a side view of the cosmetic applicator shown in FIG. 1;

FIG. 4 is an opposite side view of the cosmetic applicator shown in FIG. 1;



FIG. 5 is a bottom view of the cosmetic applicator shown in FIG. 1;

FIG. 6 is a left end view of the cosmetic applicator shown in FIG. 3; and,

FIG. 7 is a right end view of the cosmetic applicator shown in FIG. 3.

The present article is a cosmetic applicator used for applying cosmetics such as mascara. It can fit, for example, with a neck portion of a container in which a liquid cosmetic material is stored. A brush part of the present article is composed of a large number of bristles helically fixed between two twisted metal core wires. The brush part has an approximately helical, screw-like shape when viewed from the top as from FIG. 2. The brush part is slightly bent so as to have an arc-like profile when viewed from the side as from FIGS. 3 and 4. The helical sections of bristles (indicated by bold dashed lines) are continuously arranged in the axial direction and extend along a same radius except at the tip portion where the bristles are tapered. Adjacent helical sections are uniformly displaced in the same rotational direction. The part indicated by solid lines is the part for which the design patent is requested. Parts drawn in phantom indicate an environmental structure that forms no part of the design to be patented.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D657,144 S *	4/2012	Autie	D4/131
D677,904 S *	3/2013	Hammer	D4/128
D678,683 S *	3/2013	Hammer	D4/128
D691,812 S *	10/2013	Roncati	D4/128
D752,874 S *	4/2016	Jacob	D4/128
D762,393 S *	8/2016	Hong	D4/128
D812,380 S *	3/2018	Poletto	D4/128

* cited by examiner




FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7