



US00D842223S

(12) **United States Design Patent** (10) **Patent No.:** **US D842,223 S**
Seguy et al. (45) **Date of Patent:** **** Mar. 5, 2019**

- (54) **MOTORCYCLE TIRE**
- (71) Applicant: **The Goodyear Tire & Rubber Company, Akron, OH (US)**
- (72) Inventors: **Julien Michel Sylvain Seguy, Riom (FR); Armand Rene Gabriel Leconte, Bigonville (LU); Yann Armand Henri Lagarde, Montlucon (FR)**
- (73) Assignee: **The Goodyear Tire & Rubber Company, Akron, OH (US)**
- (**) Term: **15 Years**
- (21) Appl. No.: **29/639,144**
- (22) Filed: **Mar. 5, 2018**
- (51) **LOC (11) Cl.** **12-15**
- (52) **U.S. Cl.**
USPC **D12/535**
- (58) **Field of Classification Search**
USPC D12/533-567
CPC B60C 2200/00; B60C 2200/10
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
- | | | | |
|--------------|---------|-----------------|---------|
| D288,424 S | 2/1987 | Kamijyo | D12/146 |
| D292,079 S | 9/1987 | Ikeda | D12/145 |
| D292,197 S | 10/1987 | Funahara | D12/146 |
| D294,924 S * | 3/1988 | Kobayashi | D12/535 |
| D298,525 S * | 11/1988 | Suzuki | D12/535 |
| D336,271 S | 6/1993 | Suzuki | D12/147 |
| D336,627 S | 6/1993 | Hirose | D12/147 |
| D337,291 S | 7/1993 | Hirose | D12/147 |
| D420,312 S * | 2/2000 | Hara | D12/535 |
| D452,202 S * | 12/2001 | Toyozawa | D12/535 |
| D464,608 S * | 10/2002 | Liu | D12/535 |
| D490,358 S | 5/2004 | Taniguchi | D12/534 |

- | | | | |
|--------------|---------|----------------------|---------|
| D490,770 S | 6/2004 | Isaka | D12/534 |
| D503,672 S | 4/2005 | Cullinan et al. | D12/534 |
| D544,433 S | 6/2007 | Itoi | D12/534 |
| D554,043 S | 10/2007 | Chapman et al. | D12/534 |
| D562,758 S | 2/2008 | Jackson et al. | D12/556 |
| D564,441 S | 3/2008 | Itoi | D12/534 |
| D565,498 S | 4/2008 | Whitney et al. | D12/534 |
| D565,500 S * | 4/2008 | Whitney | D12/535 |
| 544,433 C1 | 6/2009 | Itoi | D12/534 |
| D595,217 S | 6/2009 | Fournier et al. | D12/535 |
| D601,942 S | 10/2009 | Bell et al. | D12/535 |
| D639,723 S * | 6/2011 | Misani | D12/535 |
| D696,623 S | 12/2013 | Nakagawa | D12/534 |
| D696,624 S | 12/2013 | Nakagawa | D12/534 |
| D717,234 S | 11/2014 | Fontaine et al. | D12/535 |
| D717,235 S | 11/2014 | Fontaine et al. | D12/535 |
| D717,724 S | 11/2014 | Fontaine et al. | D12/535 |
| D718,702 S * | 12/2014 | Winkelman | D12/535 |
| D719,082 S * | 12/2014 | Winkelman | D12/535 |
| D750,111 S | 2/2016 | Fontaine et al. | D12/535 |
| D750,549 S | 3/2016 | Ueda | D12/535 |
| D750,550 S | 3/2016 | Ueda | D12/535 |

(Continued)

Primary Examiner — George D. Kirschbaum
Assistant Examiner — Joseph J. Kukella
(74) *Attorney, Agent, or Firm* — Robert N. Lipsik

(57) **CLAIM**
The ornamental design for a motorcycle tire, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a motorcycle tire showing our new design, it being understood that the pattern repeats uniformly throughout the circumference of the tread; FIG. 2 is a front elevational view thereof; FIG. 3 is a right side elevational view thereof; the left side elevational view being a mirror image thereof; and, FIG. 4 is an enlarged fragmentary front elevational view thereof.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D754,057 S	4/2016	Pisarzewicz et al.	D12/536
D754,585 S	4/2016	Otani et al.	D12/535
D754,586 S	4/2016	Otani et al.	D12/535

* cited by examiner



FIG - 1




FIG - 2




FIG - 3




FIG - 4