US00D843955S

(12) United States Design Patent

Enger

(10) Patent No.: US D843,955 S
(45) Date of Patent: ** Mar. 26, 2019

(54) **FUSE LOCK OUT DEVICE**

(71) Applicant: **Brady Worldwide, Inc.**, Milwaukee, WI (US)

(72) Inventor: **Andrew N. Enger**, Muskego, WI (US)

(73) Assignee: **Brady Worldwide, Inc.**, Milwaukee, WI (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/615,388**

(22) Filed: **Aug. 29, 2017**

(51) **LOC (11) Cl.** **13-03**

(52) **U.S. Cl.**
USPC **D13/178**

(58) **Field of Classification Search**
USPC D13/161, 173, 178; D8/330, 331, 394; 439/135
CPC H01H 9/00; H01H 9/283; H01H 9/286; H01H 85/02; H01H 85/0208; H01H 85/24; H01R 13/44; H01R 13/443; H01R 13/465
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,207,590	A	5/1993	Benda	
D365,547	S *	12/1995	Steinwachs	D13/178
5,751,208	A *	5/1998	Martinez	H01H 85/0208 337/194
6,469,264	B2 *	10/2002	Benda	H01H 9/282 200/43.14
6,630,626	B2 *	10/2003	Johnson	H01H 85/0208 174/138 F
D564,337	S *	3/2008	Brojanac	D13/178
D564,859	S *	3/2008	Brojanac	D13/178

(Continued)

Primary Examiner — Selina Sikder

(74) *Attorney, Agent, or Firm* — Quarles & Brady LLP

(57) **CLAIM**

The fuse lock out device, as shown and described.

DESCRIPTION

FIG. **1** is a top, rear, and right perspective view of a fuse lock out device in a closed position;
FIG. **2** is a rear elevational view of the fuse lock out device of FIG. **1**;
FIG. **3** is a front elevational view of the fuse lock out device of FIG. **1**;
FIG. **4** is a right elevational view of the fuse lock out device of FIG. **1**;
FIG. **5** is a left elevational view of the fuse lock out device of FIG. **1**;
FIG. **6** is a top plan view of the fuse lock out device of FIG. **1**;
FIG. **7** is a bottom plan view of the fuse lock out device of FIG. **1**;
FIG. **8** is a top, rear, and right perspective view of a fuse lock out device from FIGS. **1-7** omitting the unclaimed sliding portion to better illustrate the covered section of the claimed portion from FIGS. **1-7**;
FIG. **9** is a rear elevational view of the fuse lock out device of FIG. **8**;
FIG. **10** is a front elevational view of the fuse lock out device of FIG. **8**;
FIG. **11** is a right elevational view of the fuse lock out device of FIG. **8**;
FIG. **12** is a left elevational view of the fuse lock out device of FIG. **8**;
FIG. **13** is a top plan view of the fuse lock out device of FIG. **8**; and,
FIG. **14** is a bottom plan view of the fuse lock out device of FIG. **8**.
The broken line representations in the views are for illustrative purposes only and form no part of the claimed design.

1 Claim, 8 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

8,629,359	B2 *	1/2014	Hackett	H01H 9/283 200/43.14
D774,870	S *	12/2016	Nasr	D8/330
D808,345	S *	1/2018	Benda	D13/178
D808,347	S *	1/2018	Benda	D13/178
10,023,130	B2 *	7/2018	Kurashina	B60R 11/06
2006/0266631	A1 *	11/2006	Kalous	H01H 9/283 200/43.14
2012/0205224	A1 *	8/2012	Hackett	H01H 9/283 200/43.14
2014/0102865	A1 *	4/2014	Obenshain	H01H 9/20 200/43.11
2014/0220802	A1 *	8/2014	Bogart	H01H 9/00 439/133
2014/0262702	A1 *	9/2014	Oley	H01H 9/283 200/43.11
2015/0206668	A1 *	7/2015	Montgomery	H01H 9/283 200/43.21

* cited by examiner



FIG. 1



FIG. 3



FIG. 2



FIG. 4



FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 10



FIG. 9



FIG. 11



FIG. 12



FIG. 13



FIG. 14