



US00D844778S

(12) **United States Design Patent** (10) **Patent No.:** **US D844,778 S**
Atkins (45) **Date of Patent:** **** Apr. 2, 2019**

- (54) **RESEALABLE AMPULE**
- (71) Applicant: **SPEX Certiprep**, Metuchen, NJ (US)
- (72) Inventor: **Patricia Lori Atkins**, Jackson, NJ (US)
- (73) Assignee: **SPEX CERTIPREP**, Metuchen, NJ (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/575,673**
- (22) Filed: **Aug. 26, 2016**

Related U.S. Application Data

- (63) Continuation of application No. 14/850,519, filed on Sep. 10, 2015, now abandoned.
- (51) **LOC (11) Cl.** **24-01**
- (52) **U.S. Cl.**
USPC **D24/121**
- (58) **Field of Classification Search**
USPC D24/121, 123, 224, 115, 117;
604/317-325; 422/558
CPC B65D 41/04; B65D 2251/023; B65D
41/0485; B65D 41/3428
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

D264,938	S *	6/1982	Stock	D24/115
4,562,043	A	12/1985	Mennen et al.		
4,635,488	A	1/1987	Kremer		
4,807,770	A *	2/1989	Barriac	B65D 41/3428 215/252
D302,722	S *	8/1989	Baxter	D24/224
D312,774	S *	12/1990	Tacconelli	D24/115
D327,950	S *	7/1992	James	D24/224
D330,598	S *	10/1992	Bottner	D24/224
D374,613	S *	10/1996	Maxwell	D24/115

(Continued)

Primary Examiner — David G Muller
(74) *Attorney, Agent, or Firm* — Kaplan Breyer Schwarz, LLP


(57) **CLAIM**

The ornamental design for a resealable ampule, as shown and described.

DESCRIPTION

FIG. 1 is a top front right isometric view of a first embodiment of a design for a resealable ampule.
 FIG. 2 is a bottom rear left isometric view of the first embodiment of the design for the resealable ampule.
 FIG. 3 is a front view of the first embodiment of the design for the resealable ampule.
 FIG. 4 is a rear view of the first embodiment of the design for the resealable ampule.
 FIG. 5 is a left view of the first embodiment of the design for the resealable ampule.
 FIG. 6 is a right view of the first embodiment of the design for the resealable ampule.
 FIG. 7 is a top view of the first embodiment of the design for the resealable ampule.
 FIG. 8 is a bottom view of the first embodiment of the design for the resealable ampule.
 FIG. 9 is a top front right isometric view of a second embodiment of a design for a resealable ampule.
 FIG. 10 is a bottom rear left isometric view of the second embodiment of the design for the resealable ampule.
 FIG. 11 is a front view of the second embodiment of the design for the resealable ampule, the back, left, and right side views being a mirror image thereof.
 FIG. 12 is a top view of the second embodiment of the design for the resealable ampule; and,
 FIG. 13 is a bottom view of the second embodiment of the design for the resealable ampule.
 The broken lines in the drawings are included for the purpose of illustrating subject matter that forms no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D379,662 S * 6/1997 Pearson D10/81
D523,141 S * 6/2006 Massey D24/121
7,182,754 B2 * 2/2007 Brigham A61M 1/0056
210/348
D629,916 S * 12/2010 Lodge D24/224
8,839,970 B2 * 9/2014 Lowry B65D 1/09
215/47
9,505,527 B1 * 11/2016 Campbell B65D 41/04

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13