



US00D848426S

(12) **United States Design Patent** (10) **Patent No.:** **US D848,426 S**  
**Nishizawa** (45) **Date of Patent:** **\*\* May 14, 2019**

(54) **COORDINATE INPUT INSTRUMENT**(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)(72) Inventor: **Naoya Nishizawa**, Setagaya-ku (JP)(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)(\*\*) Term: **15 Years**(21) Appl. No.: **29/634,759**(22) Filed: **Jan. 24, 2018**(30) **Foreign Application Priority Data**

Jul. 24, 2017 (JP) ..... 2017-015890

(51) **LOC (11) Cl.** ..... **14-02**(52) **U.S. Cl.**  
USPC ..... **D14/411**(58) **Field of Classification Search**  
USPC ..... D14/372, 496, 432, 371, 125, 126, 129,  
D14/299, 411; D16/300-342; 351/158,  
351/153, 144; 345/7-9, 905; 455/344;  
348/115, 53, 121, 739CPC ..... G02B 27/017; G06F 3/016; G06F 3/033;  
G06F 3/0317; G06F 3/03545; G06F  
3/041; G06K 9/222

See application file for complete search history.

(56) **References Cited****U.S. PATENT DOCUMENTS**

D527,050 S 8/2006 Hirota  
D614,622 S 4/2010 Nakata  
D617,327 S 6/2010 Crisp  
D699,723 S 2/2014 Nishizawa  
D708,617 S \* 7/2014 Nakata ..... D14/411  
D717,301 S \* 11/2014 Groene ..... D14/411  
D717,798 S \* 11/2014 Groene ..... D14/411  
D777,726 S \* 1/2017 Nishizawa ..... D14/411  
D781,293 S \* 3/2017 Mitchell ..... D14/411

D784,991 S \* 4/2017 Chang ..... D14/411  
D797,741 S \* 9/2017 Cebe ..... D14/411  
D799,487 S 10/2017 Nishizawa  
D812,057 S \* 3/2018 Lehman ..... D14/411  
D812,058 S \* 3/2018 Lehman ..... D14/411  
D812,059 S \* 3/2018 Lehman ..... D14/411  
D812,060 S \* 3/2018 Lehman ..... D14/411  
D826,940 S \* 8/2018 Nishizawa ..... D14/411  
D832,255 S \* 10/2018 Jung ..... D14/411  
D832,840 S \* 11/2018 Shi ..... D14/411  
D835,106 S \* 12/2018 Hsu ..... D14/411

**FOREIGN PATENT DOCUMENTS**

JP D1513748 S 12/2014  
JP D1553034 S 7/2016

\* cited by examiner

*Primary Examiner* — Austin Murphy(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC(57) **CLAIM**

The ornamental design for a coordinate input instrument, as shown and described.

**DESCRIPTION**

FIG. 1 is a top-front-right perspective view of a representative embodiment of a coordinate input instrument according to my new design;

FIG. 2 is a bottom-rear-left perspective view thereof;

FIG. 3 is a right side elevational view thereof, wherein the left side elevational view is a mirror image of the right side elevational view;


FIG. 4 is a top plan view thereof;


FIG. 5 is a bottom plan view thereof;

FIG. 6 is a front elevational view thereof; and,


FIG. 7 is a rear elevational view thereof.

The dashed broken lines in the drawings show portions of the coordinate input instrument that form no part of the claimed design.


**1 Claim, 3 Drawing Sheets**




**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**



**FIG. 7**



**FIG. 6**