



US00D848426S

(12) **United States Design Patent**
Nishizawa

(10) **Patent No.:** **US D848,426 S**

(45) **Date of Patent:** **** May 14, 2019**

(54) **COORDINATE INPUT INSTRUMENT**

(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)

(72) Inventor: **Naoya Nishizawa**, Setagaya-ku (JP)

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/634,759**

(22) Filed: **Jan. 24, 2018**

(30) **Foreign Application Priority Data**

Jul. 24, 2017 (JP) 2017-015890

(51) **LOC (11) Cl.** **14-02**

(52) **U.S. Cl.**
USPC **D14/411**

(58) **Field of Classification Search**
USPC D14/372, 496, 432, 371, 125, 126, 129,
D14/299, 411; D16/300-342; 351/158,
351/153, 144; 345/7-9, 905; 455/344;
348/115, 53, 121, 739

CPC G02B 27/017; G06F 3/016; G06F 3/033;
G06F 3/0317; G06F 3/03545; G06F
3/041; G06K 9/222

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D527,050 S	8/2006	Hirota	
D614,622 S	4/2010	Nakata	
D617,327 S	6/2010	Crisp	
D699,723 S	2/2014	Nishizawa	
D708,617 S *	7/2014	Nakata	D14/411
D717,301 S *	11/2014	Groene	D14/411
D717,798 S *	11/2014	Groene	D14/411
D777,726 S *	1/2017	Nishizawa	D14/411
D781,293 S *	3/2017	Mitchell	D14/411

D784,991 S *	4/2017	Chang	D14/411
D797,741 S *	9/2017	Cebe	D14/411
D799,487 S	10/2017	Nishizawa	
D812,057 S *	3/2018	Lehman	D14/411
D812,058 S *	3/2018	Lehman	D14/411
D812,059 S *	3/2018	Lehman	D14/411
D812,060 S *	3/2018	Lehman	D14/411
D826,940 S *	8/2018	Nishizawa	D14/411
D832,255 S *	10/2018	Jung	D14/411
D832,840 S *	11/2018	Shi	D14/411
D835,106 S *	12/2018	Hsu	D14/411

FOREIGN PATENT DOCUMENTS

JP	D1513748 S	12/2014
JP	D1553034 S	7/2016

* cited by examiner

Primary Examiner — Austin Murphy

(74) *Attorney, Agent, or Firm* — Christensen O'Connor Johnson Kindness PLLC

(57) **CLAIM**

The ornamental design for a coordinate input instrument, as shown and described.

DESCRIPTION

FIG. 1 is a top-front-right perspective view of a representative embodiment of a coordinate input instrument according to my new design;

FIG. 2 is a bottom-rear-left perspective view thereof;

FIG. 3 is a right side elevational view thereof, wherein the left side elevational view is a mirror image of the right side elevational view;

FIG. 4 is a top plan view thereof;



FIG. 5 is a bottom plan view thereof;

FIG. 6 is a front elevational view thereof; and,

FIG. 7 is a rear elevational view thereof.

The dashed broken lines in the drawings show portions of the coordinate input instrument that form no part of the claimed design.

1 Claim, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6