



US00D852335S

(12) **United States Design Patent**  
**Copeland**

(10) **Patent No.:** **US D852,335 S**  
(45) **Date of Patent:** **\*\* Jun. 25, 2019**

- (54) **RESTRAINED GASKET**
- (71) Applicant: **McWane, Inc.**, Birmingham, AL (US)
- (72) Inventor: **Daniel A. Copeland**, Bessemer, AL (US)
- (73) Assignee: **McWane, Inc.**, Birmingham, AL (US)
- (\*\*) Term: **15 Years**
- (21) Appl. No.: **29/618,093**
- (22) Filed: **Sep. 19, 2017**
- (51) **LOC (11) Cl.** ..... **23-01**
- (52) **U.S. Cl.**  
USPC ..... **D23/269**
- (58) **Field of Classification Search**  
USPC ..... D23/259, 269, 262; 277/305, 311, 314, 277/316, 351-354, 357-358, 361-364, 277/374, 382, 393-395, 397, 399, 277/416-420, 433-434, 458, 465, 479, 277/487, 504, 512, 521, 543-549, 277/562-563, 572, 604, 632; 285/105, 285/110, 337, 339, 368, 374  
CPC .... F16J 15/02; F16J 15/06; F16J 15/08; F16J 15/18; F16J 15/20; F16J 15/24; F16J 15/106; F16J 15/164; F16J 15/441; F16J 15/025; F16J 15/10; F16J 15/061; F16J 15/002; F16J 15/102; F16J 15/104; F16L 15/121; F16L 21/007; F16L 21/08; F16L 21/035; F16L 21/04; F16L 9/045; F16L 37/0845  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 2,954,264 A \* 9/1960 Tisch ..... F16J 15/32 277/630
- D391,628 S \* 3/1998 Carwile ..... D23/269

- D472,143 S \* 3/2003 Martin ..... D9/434
- D557,386 S \* 12/2007 Darce ..... D23/269
- D649,986 S \* 12/2011 Fujikata ..... D15/138
- D659,175 S \* 5/2012 Fujikata ..... D15/138
- 8,235,427 B2 \* 8/2012 Jones ..... F16L 37/0845 285/339
- 8,857,861 B2 \* 10/2014 German ..... F16L 37/0845 285/105
- 9,856,984 B2 \* 1/2018 Watanabe ..... F16J 15/164
- 2005/0040645 A1 \* 2/2005 Jones ..... F16L 21/04 285/105
- 2014/0131952 A1 \* 5/2014 Kirov ..... F16J 15/16 277/306

(Continued)

*Primary Examiner* — Eric L Goodman  
*Assistant Examiner* — Amy C Wierenga  
 (74) *Attorney, Agent, or Firm* — C. Brandon Browning; Maynard, Cooper & Gale, PC


(57) **CLAIM**

The ornamental design for a restrained gasket, as shown and described herein.

**DESCRIPTION**

FIG. 1 is a front perspective view of a first side of the restrained gasket,  
 FIG. 2 is a front perspective view a second side of the restrained gasket,  
 FIG. 3 is a rear perspective view of the second side of the restrained gasket,  
 FIG. 4 is a rear perspective view of the first side of the restrained gasket,  
 FIG. 5 is a sectional view taken along line 5-5 of FIG. 1; and,  
 FIG. 6 is an enlarged detail portion view taken from FIG. 5. The broken lines shown in the drawings are for the purpose of illustrating portions of the restrained gasket that form no part of the claim. The dot dash broken line indicates cutoff boundaries for the enlarged detail portion views that form no part of the claim.

**1 Claim, 6 Drawing Sheets**




(56)

**References Cited**


U.S. PATENT DOCUMENTS

2015/0167846 A1\* 6/2015 Haynes ..... F16J 15/442  
277/350  
2015/0204468 A1\* 7/2015 Jones ..... F16L 17/035  
285/110  
2017/0138483 A1\* 5/2017 Watanabe ..... F16J 15/164

\* cited by examiner



*FIG. 1*



*FIG. 2*





FIG. 3



*FIG. 4*




FIG. 5




FIG. 6