



US00D852336S

(12) **United States Design Patent**
Copeland

(10) **Patent No.:** **US D852,336 S**

(45) **Date of Patent:** **** Jun. 25, 2019**

- (54) **RESTRAINED GASKET**
- (71) Applicant: **McWane, Inc.**, Birmingham, AL (US)
- (72) Inventor: **Daniel A. Copeland**, Bessemer, AL (US)
- (73) Assignee: **McWane, Inc.**, Birmingham, AL (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/618,096**
- (22) Filed: **Sep. 19, 2017**
- (51) **LOC (11) Cl.** **23-01**
- (52) **U.S. Cl.**
USPC **D23/269**
- (58) **Field of Classification Search**
USPC D23/259, 269, 262; 277/305, 311, 314, 277/316, 351-354, 357-358, 361-364, 277/374, 382, 393-395, 397, 399, 277/416-420, 433-434, 458, 465, 479, 277/487, 504, 512, 521, 543-549, 277/562-563, 572, 604, 632; 285/105, 285/110, 337, 339, 368, 374
CPC F16J 15/02; F16J 15/06; F16J 15/08; F16J 15/18; F16J 15/20; F16J 15/24; F16J 15/106; F16J 15/164; F16J 15/441; F16J 15/025; F16J 15/10; F16J 15/061; F16J 15/002; F16J 15/102; F16J 15/104; F16L 15/121; F16L 21/007; F16L 21/08; F16L 21/035; F16L 21/04; F16L 9/045; F16L 37/0845
See application file for complete search history.

D557,386 S *	12/2007	Darce	D23/269
D649,986 S *	12/2011	Fujikata	D15/138
D659,175 S *	5/2012	Fujikata	D15/138
8,235,427 B2 *	8/2012	Jones	F16L 37/0845
				285/339
8,857,861 B2 *	10/2014	German	F16L 37/0845
				285/105
9,057,467 B2 *	6/2015	Copeland	F16L 37/0845
9,400,071 B1 *	7/2016	Copeland	F16L 37/0845
2005/0040645 A1 *	2/2005	Jones	F16L 21/04
				285/105
2015/0167846 A1 *	6/2015	Haynes	F16J 15/442
				277/350

(Continued)

Primary Examiner — Eric L Goodman
Assistant Examiner — Amy C Wierenga
 (74) *Attorney, Agent, or Firm* — C. Brandon Browning;
 Maynard, Cooper & Gale, PC


(57) **CLAIM**

The ornamental design for a restrained gasket, as shown and described herein.

DESCRIPTION

FIG. 1 is a front perspective view of a first side of the restrained gasket,
 FIG. 2 is a front perspective view a second side of the restrained gasket,
 FIG. 3 is a rear perspective view of the second side of the restrained gasket,
 FIG. 4 is a rear perspective view of the first side of the restrained gasket,
 FIG. 5 is a sectional view taken along line 5-5 of FIG. 1; and,
 FIG. 6 is an enlarged detail portion view taken from FIG. 5. The broken lines shown in the drawings are for the purpose of illustrating portions of the restrained gasket that form no part of the claim. The dot dash broken line indicates cutoff boundaries for the enlarged detail portion views that form no part of the claim.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0204468 A1* 7/2015 Jones F16L 17/035
285/110
2017/0138483 A1* 5/2017 Watanabe F16J 15/164

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6