



US00D852459S

(12) **United States Design Patent** (10) **Patent No.:** **US D852,459 S**
Stein (45) **Date of Patent:** **** Jul. 2, 2019**

(54) **ADJUSTABLE BRA**
(71) Applicant: **Cheryl Ann Stein**, Vancouver (CA)
(72) Inventor: **Cheryl Ann Stein**, Vancouver (CA)
(73) Assignee: **Cheryl A. Stein**, Vancouver, BC (CA)
(**) Term: **15 Years**
(21) Appl. No.: **29/651,089**
(22) Filed: **Dec. 6, 2017**
(51) **LOC (11) Cl.** **02-01**
(52) **U.S. Cl.**
USPC **D2/706**
(58) **Field of Classification Search**
USPC 450/63-64, 69, 71, 86; D2/706-708,
D2/737, 731, 703
CPC .. A41C 1/00; A41C 3/00; A41D 13/05; A41D
13/005; A41D 1/00; A41D 1/06; A41D
7/00; A41D 7/001; A41D 7/005; A41D
7/006
See application file for complete search history.

D632,610 S * 2/2011 Corrado D11/208
7,938,711 B1 * 5/2011 Johnston A41F 1/006
450/1
8,317,569 B2 11/2012 Fisher-Pacheco
D678,659 S * 3/2013 Lopez D2/708
8,651,917 B2 2/2014 Lopez et al.
8,668,549 B2 3/2014 Solotoff
9,173,435 B2 11/2015 Bailey et al.
D763,545 S 8/2016 Morin
9,788,578 B2 10/2017 Betts
D804,778 S 12/2017 Jameson
(Continued)

Primary Examiner — Robin V Webster
Assistant Examiner — J. Thorn, Sr.

(57) **CLAIM**


I claim the ornamental design for an adjustable bra, as shown and described.

DESCRIPTION

FIG. 1 is a Rear elevational view of an adjustable bra showing my new design
FIG. 2 is an exploded Rear elevational view thereof
FIG. 3 is a Front elevational view thereof
FIG. 4 is a Front elevational view thereof
FIG. 5 is a Right side elevational view thereof
FIG. 6 is a Left side elevational view thereof
FIG. 7 is a Top elevational view thereof
FIG. 8 is a Bottom elevational view thereof; and,
FIG. 9 is a Rear elevational view thereof.
The broken lines shown in the drawings are included for the purpose of illustrating environmental structure and form no part of the claimed design.
Around the torso, the back band of the bra has each free end folding over upon itself in the middle between the two shoulder blades and hooked by hook and loops (or snaps, etc) to correct adjustment size for wearer. This has a buckle in the centre to hold the two ends. The shoulder straps may also criss cross.

1 Claim, 9 Drawing Sheets

(56) **References Cited**
U.S. PATENT DOCUMENTS
2,202,058 A * 5/1940 Malnick A41C 3/00
450/59
D126,641 S * 4/1941 Rosenthal D2/708
D175,065 S * 7/1955 Brandt D2/708
3,082,771 A * 3/1963 Bruno A41C 3/00
450/70
D238,908 S * 2/1976 Guberman D2/707
5,863,236 A 1/1999 Johnson
6,023,785 A 2/2000 Johnson
6,059,633 A 5/2000 Currier
D475,506 S 6/2003 Hoffman et al.
D475,835 S 6/2003 Hoffman et al.
7,232,359 B1 6/2007 Richardson
7,435,155 B2 10/2008 Reinisch et al.
D599,081 S * 9/2009 Heer D2/706



(56)

References Cited

U.S. PATENT DOCUMENTS

D804,779	S	12/2017	Shaham	
D806,361	S *	1/2018	Grannis	D2/737
D811,934	S *	3/2018	Martinet	D11/218
2009/0258572	A1 *	10/2009	Chayo	A41C 3/0028
				450/39
2011/0055994	A1 *	3/2011	Chiaramonte	A41C 3/00
				2/67
2012/0244783	A1 *	9/2012	Lin	A41C 3/005
				450/86
2013/0068147	A1 *	3/2013	Cheung	A41F 1/006
				112/406
2016/0037845	A1 *	2/2016	Fung	A41C 3/0028
				450/92
2016/0286868	A1	10/2016	Cardaci	
2017/0035130	A1 *	2/2017	Hazzard	A41F 15/002
2017/0079334	A1 *	3/2017	Garcia	A41C 3/0028
2017/0164672	A1 *	6/2017	Fildan	A41F 1/006
2017/0273378	A1 *	9/2017	Parker-Austin	A44B 11/04
2018/0077984	A1 *	3/2018	Fildan	A41F 1/006

* cited by examiner




FIG 1




FIG 2




FIG 3




FIG 4




FIG 5




FIG 6




FIG 7




FIG 8




FIG 9