



US00D854769S

(12) **United States Design Patent**
de Ferney

(10) **Patent No.:** **US D854,769 S**

(45) **Date of Patent:** **** Jul. 23, 2019**

(54) **DUSTPAN COMPRISING A DEVICE
ALLOWING A REMOVABLE HANDLE TO
BE FITTED THERETO**

D677,849 S * 3/2013 Petersen D32/74
D695,471 S * 12/2013 Buhagiar D30/162
D795,520 S * 8/2017 La Selva D32/74

* cited by examiner

(71) Applicant: **GÏRART DE FERNEY**
(NÏCHAGNOUX GÏRARD), Ferney
Voltaire (FR)

Primary Examiner — Micheal A. Pratt

(72) Inventor: **Gérart de Ferney**, Ferney-Voltaire (FR)

(57) **CLAIM**

Ornamental design for a dustpan comprising a device allow-
ing a removable handle to be fitted thereto, as shown and
described.

(**) Term: **15 Years**

DESCRIPTION

(21) Appl. No.: **35/502,910**

(22) Filed: **Mar. 22, 2017**

The patent or application file contains at least one drawing
executed in color. Copies of this patent or patent application
publication with color drawing(s) will be provided by the
Office upon request and payment of the necessary fee.

(80) **Hague Agreement Data**

Int. Filing Date: **Mar. 22, 2017**

Int. Reg. No.: **DM/095751**

Int. Reg. Date: **Mar. 22, 2017**

Int. Reg. Pub. Date: **May 5, 2017**

1. Dustpan comprising a device allowing a removable
handle to be fitted thereto

1.1 is a perspective

1.2 is a perspective of the dust pan.

1.3 is an enlarged perspective view of the dustpan and
handle.

1.4 is an enlarged perspective view of the dustpan and
handle.

1.5 is a greatly enlarged view of a portion of the dustpan.

1.6 is a perspective view of the handle.

Dustpan with handle having a system that allows a second
vertical handle to be attached with a simple clip; left-hand
and right-hand flanges allowing the dustpan to be held in
place with the feet, leaving both hands free; without bending
down, the dustpan is secured on the ground, but extends up
to the desired height; view 1: handle with “Pelgé” system
and, at the other end, a standard screw thread that can be
fitted to any brush; view 3: attachment position; view 4:
lease; view 5: flanges with logo, two grooves to the rear of
the dustpan lock the system using a simple movement
towards the ground, with a slight forward movement being
used to release same.

(51) **LOC (11) Cl.** **07-05**

(52) **U.S. Cl.**
USPC **D32/74**

(58) **Field of Classification Search**

USPC D32/74; D30/162; D7/691, 688;
D4/116

CPC A47L 13/52; A47L 13/51; A46B 15/00;
A46B 15/0097; A46B 15/0095; A46B
17/04; A46B 5/00; A46B 2200/302


See application file for complete search history.

(56) **References Cited**


U.S. PATENT DOCUMENTS

D427,739 S * 7/2000 Demore D32/74
D463,643 S * 9/2002 Petner D32/74
D555,316 S * 11/2007 Hay D32/74
D630,401 S * 1/2011 Libman D32/74
D667,192 S * 9/2012 Libman D32/74
D673,340 S * 12/2012 Dobson, III D32/74


1 Claim, 6 Drawing Sheets
(6 of 6 Drawing Sheet(s) Filed in Color)




1.1




1.2



1.3




1.4



1.5





1.6