



US00D857859S

(12) **United States Design Patent**
Copeland et al.

(10) **Patent No.:** **US D857,859 S**

(45) **Date of Patent:** **** Aug. 27, 2019**

(54) **RESTRAINED GASKET**

(71) Applicant: **McWane, Inc.**, Birmingham, AL (US)

(72) Inventors: **Daniel A. Copeland**, Bessemer, AL (US); **Michael C. Keel**, Birmingham, AL (US)

(73) Assignee: **McWane, Inc.**, Birmingham, AL (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/610,412**

(22) Filed: **Jul. 12, 2017**

(51) **LOC (12) Cl.** **23-01**

(52) **U.S. Cl.**
USPC **D23/269**

(58) **Field of Classification Search**
USPC D23/259, 269, 262; 277/305, 311, 314, 277/316, 351-354, 357-358, 361-364, 277/374, 382, 393-395, 397, 399, 277/416-420, 433-434, 458, 465, 479, 277/487, 504, 512, 521, 543-549, 277/562-563, 572, 604, 632; 285/105, 285/110, 337, 339, 368, 374
CPC F16J 15/02; F16J 15/06; F16J 15/08; F16J 15/18; F16J 15/20; F16J 15/24; F16J 15/106; F16J 15/164; F16J 15/441; F16J 15/025; F16J 15/10; F16J 15/061; F16J 15/002; F16J 15/102; F16J 15/104; F16L 15/121; F16L 21/007; F16L 21/08; F16L 21/035; F16L 21/04; F16L 9/045; F16L 37/0845

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,954,264 A * 9/1960 Tisch F16J 15/32
277/630
D358,988 S * 6/1995 Nolte D9/434

D391,628 S * 3/1998 Carwile D23/269
D472,143 S * 3/2003 Martin D9/434
D557,386 S * 12/2007 Darce D23/269
D649,986 S * 12/2011 Fujikata D15/138
8,096,585 B2 * 1/2012 Vitel F16L 17/035
285/110
D659,175 S * 5/2012 Fujikata D15/138
9,856,984 B2 * 1/2018 Watanabe F16J 15/164
2014/0131952 A1 * 5/2014 Kirov F16J 15/16
277/306
2015/0167846 A1 * 6/2015 Haynes F16J 15/442
277/350

(Continued)

Primary Examiner — Eric L Goodman

Assistant Examiner — Amy C Wierenga

(74) *Attorney, Agent, or Firm* — C. Brandon Browning;
Maynard, Cooper & Gale, PC

(57) **CLAIM**

The ornamental design for an restrained gasket, as shown and described herein.

DESCRIPTION

FIG. 1 is a perspective view of a first side of a front of the restrained gasket.

FIG. 2 is a perspective view of a second side of the front of the restrained gasket of FIG. 1.



FIG. 3 is a perspective view of the first side of a back of the restrained gasket of FIG. 1.

FIG. 4 is a perspective view of the second side of the back of the restrained gasket of FIG. 1.

FIG. 5 is a sectional view of the restrained gasket of FIG. 1, taken along line 5-5 of FIG. 1; and,

FIG. 6 is an enlarged detail portion view taken from FIG. 5. The broken lines shown in the drawings are for the purpose of illustrating portions of the restrained gasket that form no part of the claim. The dot dash broken line indicates cutoff boundaries for the enlarged detail view that form no part of the claim.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0204468 A1* 7/2015 Jones F16L 17/035
285/110
2017/0138483 A1* 5/2017 Watanabe F16J 15/164
2017/0370505 A1* 12/2017 Copeland F16L 37/0845

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6