



US00D861794S

(12) **United States Design Patent**
Crohn et al.

(10) **Patent No.:** **US D861,794 S**
(45) **Date of Patent:** **** Oct. 1, 2019**

(54) **INDICATOR FOR A CONTAINER**
(71) Applicant: **ISP Investments LLC**, Wilmington, DE (US)
(72) Inventors: **Robert Crohn**, Towaco, NJ (US);
Rosemarie Fairman, Towaco, NJ (US)
(73) Assignee: **ISP INVESTMENTS LLC**,
Wilmington, DE (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/617,507**

(22) Filed: **Sep. 14, 2017**

(51) **LOC (12) Cl.** **19-08**

(52) **U.S. Cl.**
USPC **D20/19; D20/27**

(58) **Field of Classification Search**
USPC D20/11, 19, 22-28, 40, 99; D10/46, 47,
D10/52, 104.1; D24/189, 217
CPC G09F 1/00; G09F 1/02; G09F 3/00; G09F
3/02; G09F 3/0291; G09F 3/0294; G09F
2003/0202; G09F 2003/0208; G09F
2003/021; G09F 2003/0211; G09F
2003/0213; G09F 2003/0216; G09F
2003/0219; G09F 2003/023; G09F
2003/0232; G09F 2003/0233; G09F
2003/0235; G09F 2003/0239; G09F
2003/0272; G09F 2003/0273; G09F
2003/0279; G01J 1/50; G01K 3/04; G01K
11/12

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,051,597 A * 9/1991 Lewis G01J 1/50
250/474.1
5,602,804 A * 2/1997 Haas G01K 3/04
116/206

D439,344 S * 3/2001 Hehenberger D20/27
D457,568 S * 5/2002 Leon D20/22
D458,642 S * 6/2002 Jackson D20/22
D580,281 S * 11/2008 Lewis G01K 1/024
D10/47
D588,029 S * 3/2009 Nakatsubo G01J 1/50
D10/52
2008/0102231 A1 * 5/2008 Adachi C08L 83/04
428/32.68
2018/0342181 A1 * 11/2018 Nicholson, Jr. G01K 1/024

* cited by examiner

Primary Examiner — Mary Ann Calabrese

(74) *Attorney, Agent, or Firm* — William J. Davis;
Nathalie Tietcheu



(57) **CLAIM**

The ornamental design for an indicator for a container, as shown and described.

DESCRIPTION

FIG. 1 is a front elevation view of a first embodiment of an indicator for a container showing our new design; FIG. 2 is left side view thereof, where the right side view being identical thereto; FIG. 3 is a top plan view thereof, where the bottom plan view being identical thereto; FIG. 4 is a rear view thereof; and, FIG. 5 is a front view of an alternate configuration of FIG. 1, wherein the indicator has been exposed to electromagnetic radiation changing its appearance. The broken lines shown in the drawings illustrate portions of the indicator for a container that form no part of the claimed design.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2



FIG. 3




FIG. 4




FIG. 5