



US00D861844S

(12) **United States Design Patent**
Yang et al.

(10) **Patent No.:** **US D861,844 S**
(45) **Date of Patent:** **** Oct. 1, 2019**

- (54) **DRIFT ELIMINATOR**
- (71) Applicant: **SPX COOLING TECHNOLOGIES, INC.**, Overland Park, KS (US)
- (72) Inventors: **Jidong Yang**, Leawood, KS (US);
Jason Stratman, Lee's Summit, MO (US); **Eric Rasmussen**, Overland Park, KS (US)
- (73) Assignee: **SPX Cooling Technologies, Inc.**, Overland Park, KS (US)

- 6,385,987 B2 5/2002 Schlom et al.
- 6,715,740 B2 4/2004 Engh et al.
- D508,561 S 8/2005 Raspotnig
- D514,210 S 1/2006 Ko
- D523,110 S * 6/2006 Anderson D23/209
- D547,428 S 7/2007 Kinney, Jr. et al.
- D562,954 S 2/2008 Brenneke et al.
- D567,343 S 4/2008 Kinney, Jr. et al.
- D581,511 S 11/2008 Rosten et al.
- D657,859 S * 4/2012 Platt D23/365
- D708,729 S * 7/2014 Platt D23/365
- D736,363 S * 8/2015 Pereira D23/354
- D761,412 S 7/2016 Strehle et al.
- D784,505 S * 4/2017 Kim D23/351

(Continued)

(**) Term: **15 Years**

Primary Examiner — Natasha Vujcic

(21) Appl. No.: **29/619,945**

(74) *Attorney, Agent, or Firm* — BakerHostetler

(22) Filed: **Oct. 3, 2017**

(57) **CLAIM**

Related U.S. Application Data

The ornamental design for a drift eliminator, as shown and described.

(62) Division of application No. 29/531,571, filed on Jun. 26, 2015, now Pat. No. Des. 813,364.

DESCRIPTION

(51) **LOC (12) Cl.** **23-04**

FIG. 1 is a front perspective view of a drift eliminator having a latticed front face according to a first preferred embodiment of the invention;

(52) **U.S. Cl.**

FIG. 2 is a front view of the drift eliminator showing latticed front face according to FIG. 1;

USPC **D23/354**

FIG. 3 is a back view of the drift eliminator according to FIG. 1;

(58) **Field of Classification Search**

USPC D23/333, 335, 341, 342, 351, 353, 354, D23/355, 356, 359, 364, 365, 370, 385, D23/386, 388, 393

FIG. 4 is a right side view of the drift eliminator according to FIG. 1;

CPC F24F 1/00; F24F 1/0007; F24F 1/02; F24F 1/08; F24F 1/42; F24F 1/56; F24F 1/60; F24F 3/044; F24F 3/048; F24F 3/16; F24F 7/00; F24F 7/04; F24F 12/001; F24F 12/006

FIG. 5 is a left side view of the drift eliminator according to FIG. 1;

See application file for complete search history.

FIG. 6 is a top view of the drift eliminator according to FIG. 1; and,

(56) **References Cited**


FIG. 7 is a bottom view of the drift eliminator according to FIG. 1.

U.S. PATENT DOCUMENTS

The broken lines in the drawings illustrate portions of the drift eliminator which forms no part of the claimed design.

- D204,314 S * 4/1966 Bright D25/100
- D255,153 S * 5/1980 Meurer D23/209

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D784,507	S	*	4/2017	Kim	D23/351
D798,831	S	*	10/2017	Anzai	D13/179
D803,367	S	*	11/2017	Petterson	D23/354
D804,005	S	*	11/2017	Spear	D23/365
D813,364	S	*	3/2018	Yang	D23/351
D841,145	S	*	2/2019	Yamaguchi	D23/365
2005/0077637	A1		4/2005	Mockry et al.		
2008/0073801	A1		3/2008	Beltz et al.		
2016/0356549	A1		12/2016	Yang et al.		

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7