



US00D861844S

(12) **United States Design Patent**
Yang et al.

(10) **Patent No.:** **US D861,844 S**
(45) **Date of Patent:** **** Oct. 1, 2019**

- (54) **DRIFT ELIMINATOR**
- (71) Applicant: **SPX COOLING TECHNOLOGIES, INC.**, Overland Park, KS (US)
- (72) Inventors: **Jidong Yang**, Leawood, KS (US);
Jason Stratman, Lee's Summit, MO (US); **Eric Rasmussen**, Overland Park, KS (US)
- (73) Assignee: **SPX Cooling Technologies, Inc.**, Overland Park, KS (US)

6,385,987 B2	5/2002	Schlom et al.	
6,715,740 B2	4/2004	Engl et al.	
D508,561 S	8/2005	Raspotnig	
D514,210 S	1/2006	Ko	
D523,110 S *	6/2006	Anderson	D23/209
D547,428 S	7/2007	Kinney, Jr. et al.	
D562,954 S	2/2008	Brenneke et al.	
D567,343 S	4/2008	Kinney, Jr. et al.	
D581,511 S	11/2008	Rosten et al.	
D657,859 S *	4/2012	Platt	D23/365
D708,729 S *	7/2014	Platt	D23/365
D736,363 S *	8/2015	Pereira	D23/354
D761,412 S	7/2016	Strehle et al.	
D784,505 S *	4/2017	Kim	D23/351

(Continued)

(**) Term: **15 Years**

(21) Appl. No.: **29/619,945**

(22) Filed: **Oct. 3, 2017**

Related U.S. Application Data

(62) Division of application No. 29/531,571, filed on Jun. 26, 2015, now Pat. No. Des. 813,364.

(51) **LOC (12) Cl.** **23-04**

(52) **U.S. Cl.**
USPC **D23/354**

(58) **Field of Classification Search**
USPC D23/333, 335, 341, 342, 351, 353, 354,
D23/355, 356, 359, 364, 365, 370, 385,
D23/386, 388, 393
CPC F24F 1/00; F24F 1/0007; F24F 1/02; F24F
1/08; F24F 1/42; F24F 1/56; F24F 1/60;
F24F 3/044; F24F 3/048; F24F 3/16;
F24F 7/00; F24F 7/04; F24F 12/001;
F24F 12/006

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D204,314 S *	4/1966	Bright	D25/100
D255,153 S *	5/1980	Meurer	D23/209

Primary Examiner — Natasha Vujcic

(74) *Attorney, Agent, or Firm* — BakerHostetler

(57) **CLAIM**

The ornamental design for a drift eliminator, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a drift eliminator having a latticed front face according to a first preferred embodiment of the invention;

FIG. 2 is a front view of the drift eliminator showing latticed front face according to FIG. 1;

FIG. 3 is a back view of the drift eliminator according to FIG. 1;

FIG. 4 is a right side view of the drift eliminator according to FIG. 1;


FIG. 5 is a left side view of the drift eliminator according to FIG. 1;

FIG. 6 is a top view of the drift eliminator according to FIG. 1; and,

FIG. 7 is a bottom view of the drift eliminator according to FIG. 1.

The broken lines in the drawings illustrate portions of the drift eliminator which forms no part of the claimed design.

1 Claim, 7 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D784,507	S	*	4/2017	Kim	D23/351
D798,831	S	*	10/2017	Anzai	D13/179
D803,367	S	*	11/2017	Petterson	D23/354
D804,005	S	*	11/2017	Spear	D23/365
D813,364	S	*	3/2018	Yang	D23/351
D841,145	S	*	2/2019	Yamaguchi	D23/365
2005/0077637	A1		4/2005	Mockry et al.		
2008/0073801	A1		3/2008	Beltz et al.		
2016/0356549	A1		12/2016	Yang et al.		

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7