



US00D863008S

(12) **United States Design Patent** (10) **Patent No.:** **US D863,008 S**
Moreau et al. (45) **Date of Patent:** **** Oct. 15, 2019**

(54) **WRENCH WITH SLOT**
(71) Applicant: **Ty-Flot, Inc.**, Manchester, NH (US)
(72) Inventors: **Darrell A. Moreau**, Manchester, NH (US); **Andre W. Moreau**, Bedford, NH (US)
(73) Assignee: **Ty-Flot, Inc.**, Manchester, NH (US)
(**) Term: **15 Years**
(21) Appl. No.: **29/622,018**
(22) Filed: **Oct. 13, 2017**
(51) **LOC (12) Cl.** **08-05**
(52) **U.S. Cl.**
USPC **D8/28**; D8/27
(58) **Field of Classification Search**
USPC D8/21-29, 107, 303, 17, 82-87, 333, D8/343, 330; 81/125.1, 124.1, 124.4, 81/177.1-177.7, 489, 436-440, 60; 16/110.1, 421, 422, 430, 431; D7/395, D7/649, 402.1, 393, 645, 401.2; D4/135, D4/138
CPC B25B 13/00; B25B 13/46
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS
3,762,244 A * 10/1973 Evans B25B 13/08 81/119
D300,000 S * 2/1989 Reinhardt D8/17
D476,868 S * 7/2003 Wright D8/28
D785,439 S * 5/2017 Baus D8/333

OTHER PUBLICATIONS
Klein Tools; Klein Tools Online Catalog; 36-Inch Round Bar with Tether Hole; <https://www.kleintools.com/catalog/round-bars/36-inch-round-bar-tether-hole>; Accessed Aug. 15, 2018; 5 pages.

Stopdrop Tooling; Stopdrop Tooling Online Catalog; Adjustable Spud Wrench for Working at Height; <http://www.stopdroptooling.com/product-details/Adjustable-Spud-Wrench-for-Working-At-Height--Stopdrop-Tooling>; Accessed Aug. 15, 2018; 2 pages.
Stopdrop Tooling; Stopdrop Tooling Online Catalog; Stopdrop Tooling Pry Bar Long Pointed End for Working at Height; <http://www.stopdroptooling.com/product-details/Stopdrop-Tooling-Pry-Bar-Long-Pointed-End-for-Working-At-Height>; Accessed Aug. 15, 2018; 2 pages.

* cited by examiner
Primary Examiner — Randall H Gholson
(74) *Attorney, Agent, or Firm* — Dicke, Billig & Czaja, PLLC

(57) **CLAIM**
We claim the ornamental design for a wrench with slot, as shown and described.

DESCRIPTION
FIG. 1 is a front perspective view of a wrench with a slot showing our new design with a captured lanyard ring within the slot in dashed lines, which captured lanyard ring is disclaimed.
FIG. 2 is a front plan view thereof.
FIG. 3 is a rear plan view thereof.
FIG. 4 is a top plan view thereof.
FIG. 5 is a bottom view thereof.
FIG. 6 is a right side view thereof.
FIG. 7 is a left side view thereof.
FIG. 8 is a front perspective view of a wrench with a slot and a captured ring within the slot.
FIG. 9 is a front plan view of FIG. 8.
FIG. 10 is a rear plan view of FIG. 8.
FIG. 11 is a top plan view of FIG. 8.
FIG. 12 is a bottom view of FIG. 8
FIG. 13 is a right side view of FIG. 8; and,
FIG. 14 is a left side view of FIG. 8.

1 Claim, 2 Drawing Sheets





