



US00D864329S

(12) **United States Design Patent**
Neahr et al.

(10) **Patent No.:** **US D864,329 S**

(45) **Date of Patent:** **** Oct. 22, 2019**

(54) **DUAL BALL GLOVE FORMER**

(71) Applicants: **Joseph S. Neahr**, Riverside, CA (US);
Heather R. Neahr, Riverside, CA (US)

(72) Inventors: **Joseph S. Neahr**, Riverside, CA (US);
Heather R. Neahr, Riverside, CA (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/626,330**

(22) Filed: **Nov. 16, 2017**

(51) **LOC (12) Cl.** **21-02**

(52) **U.S. Cl.**
USPC **D21/780; D21/707; D21/719**

(58) **Field of Classification Search**
USPC D21/698, 780, 466, 707-714, 717, 719,
D21/722, 723, 725, 753, 789, 791, 799.1;
D24/211; D8/14, 77; D29/123;
D30/160; 473/415, 417, 423-430, 437,
473/506-508, 516, 575, 576, 596, 614,
473/615; 223/25, 78; 2/19, 910
CPC ... A63B 43/02; A63B 43/007; A63B 69/0079;
A63B 69/0082; A63B 69/0084; A63B
69/0086; A63B 69/0088; A63B
2069/0011; A63B 71/0045; A63B 71/14;
A63B 71/143; D06F 59/04
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D127,690 S * 6/1941 Baxter D21/466
- 2,942,883 A 6/1960 Moore
- 3,140,871 A * 7/1964 Liquori A63B 5/22
446/26
- 4,765,519 A * 8/1988 Groves A63B 71/143
2/19
- 4,793,612 A * 12/1988 Hammond A63B 69/0079
473/429
- 4,867,451 A * 9/1989 Mitchell A63B 43/02
473/576

- D326,493 S * 5/1992 Perry D21/791
- D357,500 S 4/1995 Mutterperl
- 5,456,390 A * 10/1995 McFarland A63B 47/00
223/78
- D373,402 S 9/1996 Williamson
- 5,743,808 A * 4/1998 Barth A63B 43/002
473/280
- 5,810,215 A * 9/1998 Plymell A63B 71/143
223/78
- D411,862 S * 7/1999 Greene D21/698
- 6,138,879 A * 10/2000 Breuner A63B 43/02
223/25
- D496,408 S 9/2004 Kessler
(Continued)

Primary Examiner — Catherine A Tuttle

(74) *Attorney, Agent, or Firm* — Kirk A. Buhler; Buhler & Associates Patenting


(57) **CLAIM**

The ornamental design for a dual ball glove former, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a dual ball glove former showing my new design;
 FIG. 2 is a front elevation view thereof;
 FIG. 3 is a rear elevation view thereof;
 FIG. 4 is a right-side elevation view thereof;
 FIG. 5 is a left side elevation view thereof;
 FIG. 6 is a bottom view thereof;
 FIG. 7 is a top plan view thereof; and,
 FIG. 8 is a front perspective view shown in an environment of use and with the cord element shifted to an alternate position.
 The broken lines in all the figures are included for the purpose of illustrating stitching and seams that form no part of the claimed design.
 The glove shown in FIG. 8 is for the convenience of illustration and forms no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D672,415 S * 12/2012 Garcia D21/707
8,574,102 B1 11/2013 Russell
D712,029 S * 8/2014 Tai D24/141
8,876,636 B2 11/2014 Rubel et al.
D746,394 S 12/2015 Fujisaki
D798,408 S * 9/2017 Grill D21/698
D809,617 S * 2/2018 Fujisaki D21/780
D822,136 S * 7/2018 Vincson, Jr. D21/780
2007/0155544 A1 7/2007 Killion
2009/0203471 A1* 8/2009 Roudybush A63B 15/00
473/424
2012/0208657 A1* 8/2012 Simpson A63B 69/0002
473/424
2013/0320050 A1* 12/2013 Elliott A63B 69/0084
223/66
2015/0096094 A1* 4/2015 Elliott A63B 69/0084
2/19
2019/0038951 A1* 2/2019 Curry A63B 71/0045

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG 4




FIG 5




FIG. 6




FIG. 7




FIG. 8