

US00D864329S

(12) **United States Design Patent**
Neahr et al.

(10) **Patent No.:** **US D864,329 S**
(45) **Date of Patent:** **** Oct. 22, 2019**

- (54) **DUAL BALL GLOVE FORMER**
- (71) Applicants: **Joseph S. Neahr**, Riverside, CA (US);
Heather R. Neahr, Riverside, CA (US)
- (72) Inventors: **Joseph S. Neahr**, Riverside, CA (US);
Heather R. Neahr, Riverside, CA (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/626,330**
- (22) Filed: **Nov. 16, 2017**
- (51) **LOC (12) Cl.** **21-02**
- (52) **U.S. Cl.**
USPC **D21/780; D21/707; D21/719**
- (58) **Field of Classification Search**
USPC D21/698, 780, 466, 707-714, 717, 719,
D21/722, 723, 725, 753, 789, 791, 799.1;
D24/211; D8/14, 77; D29/123;
D30/160; 473/415, 417, 423-430, 437,
473/506-508, 516, 575, 576, 596, 614,
473/615; 223/25, 78; 2/19, 910
CPC ... A63B 43/02; A63B 43/007; A63B 69/0079;
A63B 69/0082; A63B 69/0084; A63B
69/0086; A63B 69/0088; A63B
2069/0011; A63B 71/0045; A63B 71/14;
A63B 71/143; D06F 59/04
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- D127,690 S * 6/1941 Baxter D21/466
- 2,942,883 A 6/1960 Moore
- 3,140,871 A * 7/1964 Liquori A63B 5/22
446/26
- 4,765,519 A * 8/1988 Groves A63B 71/143
2/19
- 4,793,612 A * 12/1988 Hammond A63B 69/0079
473/429
- 4,867,451 A * 9/1989 Mitchell A63B 43/02
473/576

- D326,493 S * 5/1992 Perry D21/791
- D357,500 S 4/1995 Mutterperl
- 5,456,390 A * 10/1995 McFarland A63B 47/00
223/78
- D373,402 S 9/1996 Williamson
- 5,743,808 A * 4/1998 Barth A63B 43/002
473/280
- 5,810,215 A * 9/1998 Plymell A63B 71/143
223/78
- D411,862 S * 7/1999 Greene D21/698
- 6,138,879 A * 10/2000 Breuner A63B 43/02
223/25
- D496,408 S 9/2004 Kessler
(Continued)

Primary Examiner — Catherine A Tuttle

(74) *Attorney, Agent, or Firm* — Kirk A. Buhler; Buhler & Associates Patenting


(57) **CLAIM**

The ornamental design for a dual ball glove former, as shown and described.

DESCRIPTION

FIG. 1 is a top perspective view of a dual ball glove former showing my new design;
 FIG. 2 is a front elevation view thereof;
 FIG. 3 is a rear elevation view thereof;
 FIG. 4 is a right-side elevation view thereof;
 FIG. 5 is a left side elevation view thereof;
 FIG. 6 is a bottom view thereof;
 FIG. 7 is a top plan view thereof; and,
 FIG. 8 is a front perspective view shown in an environment of use and with the cord element shifted to an alternate position.
 The broken lines in all the figures are included for the purpose of illustrating stitching and seams that form no part of the claimed design.
 The glove shown in FIG. 8 is for the convenience of illustration and forms no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D672,415	S *	12/2012	Garcia	D21/707
8,574,102	B1	11/2013	Russell	
D712,029	S *	8/2014	Tai	D24/141
8,876,636	B2	11/2014	Rubel et al.	
D746,394	S	12/2015	Fujisaki	
D798,408	S *	9/2017	Grill	D21/698
D809,617	S *	2/2018	Fujisaki	D21/780
D822,136	S *	7/2018	Vincson, Jr.	D21/780
2007/0155544	A1	7/2007	Killion	
2009/0203471	A1 *	8/2009	Roudybush	A63B 15/00 473/424
2012/0208657	A1 *	8/2012	Simpson	A63B 69/0002 473/424
2013/0320050	A1 *	12/2013	Elliott	A63B 69/0084 223/66
2015/0096094	A1 *	4/2015	Elliott	A63B 69/0084 2/19
2019/0038951	A1 *	2/2019	Curry	A63B 71/0045

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG 4




FIG 5




FIG. 6




FIG. 7




FIG. 8