



US00D866291S

(12) **United States Design Patent** (10) **Patent No.:** **US D866,291 S**
Morstatt et al. (45) **Date of Patent:** **** Nov. 12, 2019**

(54) TRIM RING LOCK	7,091,429 B2 * 8/2006 Case E05B 15/02 200/314
(71) Applicant: Yale Security Inc. , Monroe, NC (US)	D552,967 S * 10/2007 Roberts D8/330 D570,188 S * 6/2008 Luo D8/330
(72) Inventors: Scott Morstatt , New Haven, CT (US); Garrett Lovejoy , New Haven, CT (US); Jason Williams , New Haven, CT (US); Jennifer Avgerinos , New Haven, CT (US)	D576,016 S * 9/2008 Min D8/330 D595,109 S * 6/2009 Doucet D8/330 D666,074 S * 8/2012 Genord D8/330 D673,153 S * 12/2012 Bousfield D14/385 D736,590 S * 8/2015 Roberts, III D8/330 D737,661 S * 9/2015 Chan D8/330 D755,605 S * 5/2016 Kraus D8/331 D768,463 S * 10/2016 Kraus D8/330
(73) Assignee: ASSA ABLOY RESIDENTIAL GROUP, INC. , New Haven, CT (US)	D779,919 S * 2/2017 Shargh D8/330 D781,130 S * 3/2017 Shargh D8/330 D783,384 S * 4/2017 Shargh D8/330 D790,956 S * 7/2017 Hetfield D8/330 D791,577 S * 7/2017 Hetfield D8/330 D818,345 S * 5/2018 Morstatt D8/330
(**) Term: 15 Years	
(21) Appl. No.: 29/646,042	

(Continued)

(22) Filed: **May 1, 2018**

Related U.S. Application Data

(62) Division of application No. 29/585,432, filed on Nov. 23, 2016, now Pat. No. Des. 818,345.

(51) **LOC (12) Cl.** **08-07**

(52) **U.S. Cl.**
USPC **D8/330**

(58) **Field of Classification Search**
USPC D8/330, 331, 336, 339, 341, 342, 343,
D8/344, 346, 350
CPC E05B 17/00; E05B 47/00; E05B 47/0001;
E05B 47/06; E05B 49/00; E05B 55/00;
E05B 63/00; E05B 65/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D271,374 S * 11/1983 Butts D8/353
6,145,353 A * 11/2000 Doucet E05B 47/0692 70/149
6,733,050 B1 * 5/2004 Yao E05B 63/044 292/137
D502,859 S * 3/2005 Peng D8/331

Primary Examiner — John Windmuller

Assistant Examiner — Steven J Czyz

(74) *Attorney, Agent, or Firm* — DeLio Peterson & Curcio LLC; Thomas E. Ciesco


(57) **CLAIM**

The ornamental design for a “trim ring lock”, as shown and described.

DESCRIPTION

FIG. 1 is a right, front, top perspective view of a trim ring lock according to our invention;
FIG. 2 is a front elevation view thereof;
FIG. 3 is a rear elevation view thereof;
FIG. 4 is a right side elevation view thereof;
FIG. 5 is a left side elevation view thereof;
FIG. 6 is a bottom elevation view thereof; and,
FIG. 7 is a top elevation view thereof.
The broken lines depict portions of the article that form no part of the claimed design.

1 Claim, 2 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D818,797	S	*	5/2018	Morstatt	D8/334
D832,077	S	*	10/2018	Gokcebay	D8/331
D835,970	S	*	12/2018	Morstatt	D8/331
D837,029	S	*	1/2019	Cavanna	D8/331
D837,030	S	*	1/2019	Cavanna	D8/331
D837,629	S	*	1/2019	Cavanna	D8/331
D837,630	S	*	1/2019	Cavanna	D8/331
D844,411	S	*	4/2019	Griswold	D8/331
D844,414	S	*	4/2019	Leites	D8/353
10,323,437	B2	*	6/2019	Hallett	E05B 63/08

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

FIG. 6




FIG. 7

