

US00D867599S

(12) **United States Design Patent** (10) **Patent No.:** **US D867,599 S**
Barbaric et al. (45) **Date of Patent:** **** Nov. 19, 2019**

(54) **WEARABLE BIOSENSING DEVICE**

(56) **References Cited**

(71) Applicant: **Empatica Srl**, Milan (IT)

U.S. PATENT DOCUMENTS

(72) Inventors: **Mladen Barbaric**, Ottawa (CA);
Minkyu Choi, Montreal (CA); **Kihyun Kim**, Ottawa (CA); **Sungmoon Kim**,
Ville-St-Laurent (CA)

4,305,401 A	12/1981	Reissmueller et al.	
D342,571 S *	12/1993	Givens, Sr.	D24/186
D402,762 S	12/1998	Szpur	
D567,950 S	4/2008	Savage, Jr.	
D605,305 S *	12/2009	Carter	D24/231
D645,360 S	9/2011	Kiser et al.	
D670,583 S	11/2012	Shaanan	
D674,488 S	1/2013	McKay et al.	
D716,457 S	10/2014	Brefka et al.	
D733,131 S *	6/2015	Kim	D14/344
D736,935 S	8/2015	Just et al.	
D737,157 S	8/2015	Akana et al.	
D746,477 S *	12/2015	Cha	D24/186

(73) Assignee: **Empatica Srl**, Milan (IT)

(**) Term: **15 Years**

(21) Appl. No.: **29/565,749**

(22) Filed: **May 24, 2016**

(Continued)

Related U.S. Application Data

Primary Examiner — Wan Laymon
Assistant Examiner — Mark Booker

(62) Division of application No. 29/509,637, filed on Nov. 19, 2014, now Pat. No. Des. 760,395.

(51) **LOC (12) Cl.** **24-01**

(57) **CLAIM**

(52) **U.S. Cl.**
USPC **D24/186**

The ornamental design for a wearable biosensing device, as shown and described.

(58) **Field of Classification Search**

DESCRIPTION


USPC D24/186, 107, 165–168, 187, 200;
D10/30, 31, 32, 70, 97, 98, 1–5, 6–10,
D10/11–15, 16–20, 121–132; D11/3, 4,
D11/224, 225; D14/341, 344;
128/DIG. 15; 600/301, 382–384, 386,
600/390, 483, 500–503, 508, 509, 513;
D19/9, 10; D21/300–304, 386, 457;
273/317, 332, 336, 342, 348, 402, 398,
273/407, 408; 473/569, 588–591
CPC A61B 5/6803; A61B 5/681; A61B 5/6824;
A61B 5/6825; A61B 5/024; A61B
5/02405; A61B 5/02438; G04B 17/00;
G04B 17/02; G04B 17/005; G04B
17/285; G04B 37/00; G04B 37/0058;
G04B 45/00; G04B 45/02; G04B 45/038;
G04B 45/0069; G04B 45/0076; G04B
29/00

FIG. 1 is a perspective view of a wearable biosensing device;
FIG. 2 is another perspective view thereof;
FIG. 3 is a front view thereof;
FIG. 4 is a back view thereof;
FIG. 5 is a top view thereof;
FIG. 6 is a bottom view thereof;
FIG. 7 is a left side view thereof; and,
FIG. 8 is a right side view.

The broken lines immediately adjacent the shaded areas represent the bounds of the claimed design while all other broken lines are directed to environment and are for illustrative purposes only; the broken lines form no part of the claimed design.

See application file for complete search history.

1 Claim, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D752,580 S *	3/2016	Choi	D10/32
D754,550 S *	4/2016	Izuka	D10/30
D760,395 S *	6/2016	Barbaric	D24/186
D761,675 S *	7/2016	Thaveeprungsriporn	D10/38
D787,960 S *	5/2017	Park	D10/39
D809,938 S *	2/2018	Hou	D10/30
2010/0036270 A1	2/2010	Chen	
2014/0135612 A1	5/2014	Yuen et al.	

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8