



US00D867924S

(12) **United States Design Patent**
Paik et al.

(10) **Patent No.:** **US D867,924 S**

(45) **Date of Patent:** **** Nov. 26, 2019**

(54) **BELT CONTROLLER FOR BAGS**

(71) Applicant: **WOOJIN PLASTIC CO., LTD.**,
Gyeonggi-do (KR)

(72) Inventors: **Jisook Paik**, Seoul (KR); **Nan Hee Paik**, Seoul (KR); **Ji Hye Paik**, Seoul (KR); **Ji Won Son**, Seoul (KR)

(73) Assignee: **WOOJIN PLASTIC CO., LTD.**, Guri si (KR)

(**) Term: **15 Years**

(21) Appl. No.: **29/631,691**

(22) Filed: **Jan. 2, 2018**

(51) **LOC (12) Cl.** **02-07**

(52) **U.S. Cl.**
USPC **D11/218**

(58) **Field of Classification Search**
USPC D2/624, 626, 627, 633, 639, 640, 853,
D2/923; D3/24, 213, 215, 216, 230;
D8/14, 331, 343, 349, 356, 358, 359, 360,
D8/363, 366, 371, 382, 394, 395;
D10/32, 38; D11/1, 2, 3, 12, 16, 86, 87,
D11/93, 200, 201, 206–210, 212–218,
D11/229–237; D12/195, 416;
D29/100–101.5, 122, 129, 130; D30/139,
D30/152, 153

CPC A44B 11/00; A44B 11/02; A44B 11/04;
A44B 11/05; A44B 11/06; A44B 11/10;
A44B 11/14; A44B 11/18; A44B 11/22;
A44B 11/25; A44B 11/26; A44B 11/125;
A44B 11/223; A44B 11/001; A44B
11/005; A44B 11/006; A44B 11/2503;
A44B 11/2507; A44B 11/2526; A44B
11/2553; A44B 11/2592; A41F 1/008;
A41F 9/002; A41F 9/007; A41F 11/06;
B60R 22/30; B60R 22/32; B60R 22/022;
B60R 2022/1806; B60R 2022/1812;
B60R 2022/281; B65D 63/16; A62B
35/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D184,191	S	*	12/1958	Noe	D11/216
D350,712	S	*	9/1994	D'Ambrosio	D11/218
D683,263	S	*	5/2013	Paik	D11/218
D702,151	S	*	4/2014	Kaneko	D11/218
D703,097	S	*	4/2014	Nanbu	D11/218
D764,348	S	*	8/2016	Paik	D11/216
D823,717	S	*	7/2018	Ho	D11/218
D840,870	S	*	2/2019	Koreishi	D11/218
2008/0078069	A1	*	4/2008	Pontaoe	A44B 11/04 24/196

FOREIGN PATENT DOCUMENTS

KR 300951705.0000 * 7/2018

* cited by examiner

Primary Examiner — Kevin K Rudzinski

Assistant Examiner — Richard Kearney



(57) **CLAIM**

We claim, the ornamental design for a belt controller for bags, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a belt controller for bags, showing our new design;
FIG. 2 is a front view thereof;
FIG. 3 is a rear view thereof;
FIG. 4 is a left side view thereof;
FIG. 5 is a right side view thereof;
FIG. 6 is a top plan view thereof;
FIG. 7 is a bottom plan view thereof;
FIG. 8 is a cross-sectional view taken along the lines A-A of FIG. 2; and,
FIG. 9 is another perspective view of the belt controller for bags in an alternate state of use.

1 Claim, 9 Drawing Sheets






FIG.1




FIG.2




FIG. 3




FIG.4




FIG.5




FIG.6




FIG.7




FIG. 8




FIG.9