



US00D870660S

(12) **United States Design Patent** (10) **Patent No.:** **US D870,660 S**
De Lauri et al. (45) **Date of Patent:** **** Dec. 24, 2019**

(54) **BATTERY CHARGER**

(71) Applicant: **ALFAZERO S.P.A.**, Milan (IT)

(72) Inventors: **Mauro De Lauri**, Florence (IT);
Giovanni Pierantoni, Florence (IT)

(73) Assignee: **ALFAZERO S.P.A.**, Milan (IT)

(**) Term: **15 Years**

(21) Appl. No.: **29/662,686**

(22) Filed: **Sep. 7, 2018**

(30) **Foreign Application Priority Data**

Mar. 7, 2018 (EM) 004744191-0002

(51) **LOC (12) Cl.** **13-02**

(52) **U.S. Cl.**
USPC **D13/108**

(58) **Field of Classification Search**
USPC D13/107-110, 118-119, 184; D14/251,
D14/253, 432, 434
CPC Y02E 60/12; Y02T 90/14; Y02T 90/122;
Y02T 90/128; Y02T 90/163; H02J 7/025;
H02J 7/0042; H02J 7/0044; H02J 7/0045;
H02J 7/0003; H01F 38/14; H01R
13/6675; H01M 2/1022; H01M 2/1055;
H01M 10/44; H01M 10/46; H01M
10/425; B60L 11/182

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D230,381 S * 2/1974 Otto D13/108
D526,973 S * 8/2006 Gates D13/168
D558,209 S * 12/2007 Ikeda D14/434
D585,898 S * 2/2009 Skurdal D14/434
D660,228 S * 5/2012 Matsuoka D13/110
D706,212 S * 6/2014 Zwierstra D13/107

D730,826 S * 6/2015 Moanack D13/110
D731,449 S * 6/2015 Norman D13/184
D757,014 S * 5/2016 Hahn D13/108
D758,304 S * 6/2016 Wright D13/107
D774,455 S * 12/2016 Kim D13/108
D787,439 S * 5/2017 Sloan D13/107
D789,373 S * 6/2017 King D14/413
D789,374 S * 6/2017 King D14/413
D794,557 S * 8/2017 Kim D13/108
D795,182 S * 8/2017 Akana D13/108
D810,015 S * 2/2018 Carreon D13/108
D832,276 S * 10/2018 Miles D14/451
D832,859 S * 11/2018 Charlesworth D14/451
D837,148 S * 1/2019 Brown D13/108
D839,188 S * 1/2019 Akana D13/108
D839,191 S * 1/2019 Akana D13/108
D841,585 S * 2/2019 Huang D13/119

* cited by examiner

Primary Examiner — Rosemary K Tarcza

(74) *Attorney, Agent, or Firm* — Andrew F. Young, Esq.;
Lackebach Siegel, LLP

(57) **CLAIM**

The ornamental design for battery charger, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a battery charger of our present invention.

FIG. 2 is a top plan view of FIG. 1.

FIG. 3 is a bottom plan view of FIG. 1.

FIG. 4 is a left-side view of FIG. 1.


FIG. 5 is a right-side view of FIG. 1.

FIG. 6 is a front view of FIG. 1; and,

FIG. 7 is a rear view of FIG. 1.

The dash-dot-dash lines in FIGS. 1-3 are for the purpose of illustrating portions of the battery charger that form no part of the claimed design. The surfaces are lightly lined for contour.

1 Claim, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7