



US00D871322S

(12) **United States Design Patent** (10) **Patent No.:** **US D871,322 S**
Nook et al. (45) **Date of Patent:** **** Dec. 31, 2019**

(54) **BATTERY JUMP STARTING DEVICE**

H01M 2/1055; H01M 10/44; H01M 10/46; H01M 10/425; B60L 11/182

See application file for complete search history.

(71) Applicant: **THE NOCO COMPANY**, Glenwillow, OH (US)

(56) **References Cited**

(72) Inventors: **Jonathan Lewis Nook**, Gates Mills, OH (US); **William Knight Nook, Sr.**, Shaker Heights, OH (US); **James Richard Stanfield**, Peoria, AZ (US); **Derek Michael Underhill**, Tempe, AZ (US)

U.S. PATENT DOCUMENTS

| | | | | | | |
|--------------|----|---|---------|---------|-------|-------------|
| D694,180 | S | * | 11/2013 | Inskeep | | D13/107 |
| D745,455 | S | * | 12/2015 | Nook | | D13/103 |
| D746,770 | S | * | 1/2016 | Nook | | D13/103 |
| D786,191 | S | * | 5/2017 | McSweyn | | D13/103 |
| D793,955 | S | * | 8/2017 | Yang | | D13/107 |
| D814,406 | S | * | 4/2018 | Yang | | D13/107 |
| D832,781 | S | * | 11/2018 | Nook | | D13/107 |
| D836,064 | S | * | 12/2018 | Liu | | D13/102 |
| D836,068 | S | * | 12/2018 | Nook | | D13/120 |
| D845,230 | S | * | 4/2019 | Nook | | D13/107 |
| 2018/0269703 | A1 | * | 9/2018 | Nook | | H01M 2/1072 |
| 2018/0342891 | A1 | * | 11/2018 | Nook | | H01M 2/30 |
| 2019/0173305 | A1 | * | 6/2019 | Nook | | F02N 11/12 |

(73) Assignee: **THE NOCO COMPANY**, Glenwillow, OH (US)

* cited by examiner

(**) Term: **15 Years**

Primary Examiner — Rosemary K Tarcza

Assistant Examiner — Nathaniel D. Buckner

(21) Appl. No.: **29/682,384**

(74) *Attorney, Agent, or Firm* — Vorys, Sater, Seymour and Pease LLP; William L. Klima

(22) Filed: **Mar. 5, 2019**

Related U.S. Application Data

(63) Continuation of application No. 29/615,035, filed on Aug. 25, 2017, now Pat. No. Des. 845,230.

(57) **CLAIM**

The ornamental design for a battery jump starting device, as shown and described.

(51) **LOC (12) Cl.** **13-02**


(52) **U.S. Cl.**
USPC **D13/107**

DESCRIPTION

(58) **Field of Classification Search**
USPC D13/106–110, 118, 184; D15/9
CPC Y02E 60/12; Y02T 90/14; Y02T 90/122;
Y02T 90/128; Y02T 90/163; Y02T 10/7005; Y02T 10/705; Y02T 10/7088;
H02J 7/025; H02J 7/0042; H02J 7/0044;
H02J 7/0045; H02J 7/0003; H02J 7/0034;
H02J 7/0054; H02J 7/1423; H02J 2001/006; H01F 38/14; H01M 2/1022;


FIG. 1 is a top right perspective view for a battery jump starting device showing our new design;
FIG. 2 is a top left perspective view thereof;
FIG. 3 is a front elevation view thereof;
FIG. 4 is a rear elevation view thereof;
FIG. 5 is a top plan view thereof;
FIG. 6 is a bottom plan view thereof;
FIG. 7 is a left side elevation view thereof; and,
FIG. 8 is a right side elevation view thereof.

(Continued)



The broken lines shown in the drawings depict portions of the article that form no part of the claimed design.

1 Claim, 8 Drawing Sheets






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8