



US00D871628S

(12) **United States Design Patent** (10) **Patent No.:** **US D871,628 S**  
**Hirata** (45) **Date of Patent:** **\*\* Dec. 31, 2019**

(54) **REAR COMBINATION LAMP FOR AN AUTOMOBILE**

D701,631 S \* 3/2014 Goto ..... D26/28  
D798,477 S \* 9/2017 Lai ..... D26/28  
D799,077 S \* 10/2017 Lai ..... D26/28

(71) Applicant: **Nissan Motor Co., Ltd.**, Yokohama, Kanagawa (JP)

\* cited by examiner

(72) Inventor: **Yusuke Hirata**, Kanagawa (JP)

*Primary Examiner* — Marcus A Jackson

(73) Assignee: **Nissan Motor Co., Ltd.**, Yokohama (JP)

(74) *Attorney, Agent, or Firm* — Global IP Counselors, LLP

(\*\*) Term: **15 Years**

(57) **CLAIM**

The ornamental design for a rear combination lamp for an automobile, as shown and described.

(21) Appl. No.: **29/663,219**

**DESCRIPTION**

(22) Filed: **Sep. 13, 2018**

FIG. 1 is a front elevational view of a rear combination lamp for an automobile in accordance with a first embodiment of our new design;

(30) **Foreign Application Priority Data**

Mar. 15, 2018 (JP) ..... 2018-005510

FIG. 2 is a rear elevational view thereof;

(51) **LOC (12) Cl.** ..... **26-06**

FIG. 3 is a top plan view thereof;

(52) **U.S. Cl.**

USPC ..... **D26/28**

FIG. 4 is a bottom plan view thereof;

(58) **Field of Classification Search**

USPC ..... D26/28-36, 139

CPC ..... F21S 48/00; F21S 48/10; F21S 48/115;

F21S 48/225; F21S 48/1233; F21S

48/1266; F21S 48/1388; F21S 48/2268;

F21V 21/04; B60Q 9/13; B60Q 9/135;

B60Q 9/1375

FIG. 5 is a left side elevational view thereof;

FIG. 6 is a right side elevational view thereof; and,

FIG. 7 is a front side perspective view thereof.

See application file for complete search history.

The rear combination lamp for an automobile is configured to be mounted to an automobile. The mounting structure and support structure of the rear combination lamp for an automobile, shown in broken lines in FIGS. 1 to 7, form no part of the claimed design since the mounting structure and support structure are hidden when the rear combination lamp for an automobile is mounted to the automobile.

In addition, the appearance of the rear side structures of the rear combination lamp for an automobile as shown in broken lines in FIGS. 2 to 4, 6 and 7 is for purpose of illustrating the boundaries of the exterior surface of the rear combination lamp for an automobile, and forms no part of the claimed design. The second embodiment of our new design includes the mirror image of the rear combination lamp for an automobile shown in FIGS. 1 to 7.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D655,429 S \* 3/2012 Fushimi ..... D26/28


D657,482 S \* 4/2012 Kong ..... D26/28

D690,849 S \* 10/2013 Kawaguchi ..... D26/28

D690,850 S \* 10/2013 Hanaoka ..... D26/28

D692,599 S \* 10/2013 Kim ..... D26/28

**1 Claim, 7 Drawing Sheets**






FIG. 1






FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7