



US00D875153S

(12) **United States Design Patent** (10) **Patent No.:** **US D875,153 S**
Kostrzewa et al. (45) **Date of Patent:** **** Feb. 11, 2020**

(54) **CAMERA CORE**

(71) Applicant: **FLIR Systems, Inc.**, Wilsonville, OR (US)

(72) Inventors: **Joseph Kostrzewa**, Buellton, CA (US);
Jared A. Faraudo, Goleta, CA (US);
Dan S. Walker, Goleta, CA (US); **Alan D. Kathman**, Charlotte, NC (US);
Marcel Tremblay, Goleta, CA (US);
Thad Lieb, Goleta, CA (US); **Bruce A. Covington**, Santa Barbara, CA (US)

(73) Assignee: **FLIR Systems, Inc.**, Wilsonville, OR (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/581,251**

(22) Filed: **Oct. 17, 2016**

(51) **LOC (12) Cl.** **16-01**

(52) **U.S. Cl.**
USPC **D16/202**; D16/219

(58) **Field of Classification Search**
USPC D16/200, 202, 203, 208, 207, 218, 219,
D16/237, 241–245; D8/354, 355, 363;
D12/114, 223; 396/419, 420, 428, 535,
396/540–541; 348/373–374
CPC F16M 11/14; F16M 11/041; F16M 11/04;
F16M 11/2078; F16M 11/28; F16M
11/2021; F16M 11/12; F16M 11/10;
F16M 2200/022; F16M 2200/027; F16M
13/00; F16M 13/02; F16M 13/022; G03B
17/561; G03B 17/566; G03B 17/563;
G03B 2215/056; B60R 2011/0059; B60R
2011/008; B60R 11/02

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D489,388 S *	5/2004	Saito	D16/200
D496,062 S *	9/2004	Yamakami	D16/200
D496,382 S *	9/2004	Yamakami	D16/200
D510,376 S *	10/2005	Yamakami	D16/200
D511,182 S *	11/2005	Kato	D16/200
D515,610 S *	2/2006	Yamakami	D16/200
D550,741 S *	9/2007	Vernon	D16/208
D564,562 S *	3/2008	Honma	D16/200

(Continued)

Primary Examiner — Ramzi S Almatrahi

(74) *Attorney, Agent, or Firm* — Haynes and Boone, LLP


(57) **CLAIM**

The ornamental design for a camera core, as shown and described.

DESCRIPTION

FIG. 1 is a front elevational view of a camera core showing our new design;
FIG. 2 is a rear elevational view thereof;
FIG. 3 is a right side view thereof;
FIG. 4 is a left side view thereof;
FIG. 5 is a top plan view thereof;
FIG. 6 is a bottom plan view thereof;
FIG. 7 is a rear, right, and bottom perspective view thereof;
FIG. 8 is an exploded front, left, and top perspective view thereof, shown in condition of use with a shutter and lens disclosed in broken lines to illustrate an environment; and,
FIG. 9 is an exploded front, left, and top perspective view of a second embodiment of a camera core, shown in condition of use with a shutter, lens, and lens holder disclosed in broken lines to illustrate an environment.
The broken lines depict portions of the camera core in which the design is embodied that form no part of the claimed design. Additionally, the broken lines showing a shutter, lens, and lens holder in FIGS. 8 and 9 represent environmental structure and form no part of the claimed design.

1 Claim, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,467,675 B2 *	6/2013	Chen	G03B 17/02 348/374
D699,775 S *	2/2014	Li	D16/200
D699,776 S *	2/2014	Li	D16/200
D774,584 S	12/2016	Walters et al.	
D788,208 S *	5/2017	Muhlenkamp, IV	D16/200
2014/0168509 A1 *	6/2014	Lee	H04N 5/2256 348/374

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9