US00D879969S

(12) United States Design Patent

Sandt et al.

(10) Patent No.: US D879,969 S
(45) Date of Patent: ** Mar. 31, 2020

(54) **DETECTION APPARATUS**

(71) Applicant: **Undercover Colors, Inc.**, Raleigh, NC (US)

(72) Inventors: **Adam Sandt**, Apex, NC (US); **Joshua Steven Joseph**, Cary, NC (US); **Nicolas Letourneau**, Raleigh, NC (US)

(73) Assignee: **Undercover Colors, Inc.**, Research Triangle Park, NC (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/647,396**

(22) Filed: **May 11, 2018**

(51) **LOC (12) Cl.** **24-01**

(52) **U.S. Cl.**
USPC **D24/186**; D10/81

(58) **Field of Classification Search**
USPC D24/107, 167, 186, 187, 112, 169; D10/70, 75, 98, 97, 81; D14/344
CPC A61B 5/6801; A61B 5/681; A61B 5/6819; A61B 5/6823; A61B 5/6824; A61B 5/02405; A61B 5/02427; A61B 5/02438; A61B 5/0245; A61B 5/0402; A61B 5/0404; A61B 5/0004; A61B 5/14503; A61B 5/14532; A61B 5/14865; A61B 5/6832; A61B 5/6833; A61B 5/6849; A61B 2560/0412; A61B 2560/0443; A61B 2560/0462; A61M 25/0206
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D632,396	S *	2/2011	Kasabach	D24/186
D719,267	S *	12/2014	Vaccarella	D24/187
D732,672	S *	6/2015	Lewis, Jr.	D24/187
D746,993	S *	1/2016	Lewis, Jr.	D24/187
D760,102	S *	6/2016	Frandsen	D10/81
D796,046	S *	8/2017	Sadot	D24/186
D796,682	S *	9/2017	Falk	D24/186
10,016,315	B2 *	7/2018	Letourneau	A61B 5/6826
D842,996	S *	3/2019	Frick	D24/169
2017/0188910	A1 *	7/2017	Halac	A61B 5/14532
2018/0027908	A1 *	2/2018	Greenly	A61B 5/486
2019/0159727	A1 *	5/2019	Macagno	A61B 5/6807

* cited by examiner

Primary Examiner — Anhdao Doan
(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **CLAIM**

The ornamental design for a detection apparatus, as shown and described.

DESCRIPTION

FIG. **1** is a top perspective view of a first embodiment of a detection apparatus comprising the present invention;
FIG. **2** is a front elevational view thereof;
FIG. **3** is a side elevational view thereof;
FIG. **4** is another side elevational view thereof;
FIG. **5** is a rear elevational view thereof;
FIG. **6** is a top plan view thereof;
FIG. **7** is a bottom plan view thereof;
FIG. **8** is a top perspective view of a second embodiment of a detection apparatus comprising the present invention;
FIG. **9** is a front elevational view thereof;
FIG. **10** is a side elevational view thereof;
FIG. **11** is another side elevational view thereof;
FIG. **12** is a rear elevational view thereof;
FIG. **13** is a top plan view thereof; and,
FIG. **14** is a bottom plan view thereof.

1 Claim, 14 Drawing Sheets





FIG. 1



FIG. 2



FIG. 3



FIG. 4



FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9



FIG. 10



FIG. 11



FIG. 12



FIG. 13



FIG. 14