



US00D882499S

(12) **United States Design Patent** (10) **Patent No.:** **US D882,499 S**
Smith et al. (45) **Date of Patent:** **** Apr. 28, 2020**

(54) **TIRE TREAD**
(71) Applicant: **The Carlstar Group LLC**, Franklin, TN (US)
(72) Inventors: **Chris Smith**, Cedar Grove, TN (US); **Richard Hogg**, Jackson, TN (US); **David Dahl**, Jackson, TN (US); **Brian Crisamore**, Milan, TN (US); **Ben Holt**, Lexington, TN (US)

D620,428 S * 7/2010 Rayman D12/579
D624,008 S * 9/2010 Shan D12/579
D648,261 S * 11/2011 Rayman D12/579
D731,959 S * 6/2015 Larregain D12/579
D743,878 S * 11/2015 Mathis D12/579
D751,974 S * 3/2016 Green D12/579
D752,505 S * 3/2016 Dhanens D12/579
D795,168 S * 8/2017 Hixson B60C 11/01
D12/579
D795,795 S * 8/2017 Robbins D12/579
D832,196 S * 10/2018 Gootjes D12/579

(73) Assignee: **The Carlstar Group LLC**, Franklin, TN (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/676,558**

(22) Filed: **Jan. 11, 2019**

(51) **LOC (12) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/579**

(58) **Field of Classification Search**
USPC D12/579, 596, 597, 602, 603
CPC B60C 11/01; B60C 11/0306; B60C 11/11
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D167,779 S * 9/1952 Steadman D12/571
D457,488 S * 5/2002 Rayman D12/579
D462,651 S * 9/2002 Rayman D12/579
D483,718 S * 12/2003 Hutz B60C 11/01
D12/579
D486,782 S * 2/2004 Fukunaga D12/579
D530,264 S * 10/2006 Labbe D12/579
D530,265 S * 10/2006 Hutz D12/579
D530,266 S * 10/2006 Hutz D12/579
D573,942 S * 7/2008 Song D12/579
D593,485 S * 6/2009 Davidson, Jr. D12/579
D604,690 S * 11/2009 Dixon D12/579
D606,928 S * 12/2009 Song D12/579
D610,071 S * 2/2010 Song D12/579

OTHER PUBLICATIONS

Camso, Camso SKS 753 Product Sheet; 2017.

* cited by examiner

Primary Examiner — Robert M. Spear

(74) *Attorney, Agent, or Firm* — Stites & Harbison PLLC; Richard S. Myers, Jr.; Sean P. Ritchie

(57) **CLAIM**

The ornamental design for a tire tread, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of the design of the tire tread of the present invention;
FIG. 2 is a front elevation view of the tire tread shown in FIG. 1;
FIG. 3 is a rear elevation view of the tire tread shown in FIG. 1;
FIG. 4 is a right side elevation view of the tire tread shown in FIG. 1;
FIG. 5 is a left side elevation view of the tire tread shown in FIG. 1;
FIG. 6 is an expanded view of a portion of the tire tread shown in FIG. 1; and,
FIG. 7 is an expanded view of a portion of the tire tread shown in FIG. 2.

1 Claim, 7 Drawing Sheets




FIG. 1




FIG. 6

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

