



US00D882503S

(12) **United States Design Patent** (10) **Patent No.:** **US D882,503 S**
Schultz et al. (45) **Date of Patent:** **** Apr. 28, 2020**

(54) **TIRE**
(71) Applicant: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)
(72) Inventors: **David E. Schultz**, Stow, OH (US);
Reubin R. Close, Rootstown, OH (US)
(73) Assignee: **Bridgestone Americas Tire Operations, LLC**, Nashville, TN (US)

D728,465 S 5/2015 Kuwahara
D735,117 S 7/2015 Koog
D739,343 S 9/2015 Gommez
D761,724 S 7/2016 Yamamoto
D762,556 S 8/2016 Dixon et al.
D765,583 S 9/2016 Wang et al.
D765,587 S 9/2016 Inoue
D768,061 S 10/2016 Cerny
D769,797 S 10/2016 Fujioka
D786,783 S 5/2017 Marlier et al.

(Continued)

(**) Term: **15 Years**

OTHER PUBLICATIONS

(21) Appl. No.: **29/671,837**

David E. Schultz, "Tire", Design U.S. Appl. No. 29/671,835, filed Nov. 30, 2018.

(22) Filed: **Nov. 30, 2018**

Primary Examiner — Robert M. Spear

(51) **LOC (12) Cl.** **12-15**

(52) **U.S. Cl.**
USPC **D12/598**

(58) **Field of Classification Search**
USPC D12/579, 596, 597, 598, 602, 603
CPC .. B60C 11/0306; B60C 11/0309; B60C 11/04
See application file for complete search history.

(57) **CLAIM**

The ornamental design for a tire, as shown and described.

(56) **References Cited**

DESCRIPTION

U.S. PATENT DOCUMENTS

2,272,879 A * 2/1942 Hargraves B60C 11/0309
152/209.22
4,913,208 A * 4/1990 Anderson B60C 11/1369
152/209.18
D308,190 S * 5/1990 Fetty B60C 11/1369
D12/602
D391,203 S * 2/1998 Gillard D12/596
D432,059 S * 10/2000 Feider D12/603
D457,128 S 5/2002 Robert et al.
D619,531 S * 7/2010 Naruo D12/598
D646,623 S 10/2011 Kojima et al.
D647,461 S 10/2011 Godeau et al.
D652,367 S 1/2012 Lange et al.
D661,245 S 6/2012 Buchinger-Barnstorf
D676,803 S * 2/2013 Bournat B60C 11/0309
D12/598
D726,644 S 4/2015 Kuwahara

This invention was made with Government support under DE-EE0007761 awarded by DOE. The Government has certain rights in this invention.

FIG. 1 is a side perspective view of a tire showing our new design, the pattern repeating uniformly around the circumference of the tire;


FIG. 2 is a front elevational view thereof;

FIG. 3 is an enlarged fragmentary view showing the details of our new design; and,

FIG. 4 is a side elevational view thereof, the right side being a mirror image.

The broken lines defining the tread lug walls, tread groove interiors, sidewall, inner bead, and the tread shoulder ribs depict environmental subject matter that forms no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D792,335 S	7/2017	Dixon et al.
D794,543 S	8/2017	Seo et al.
D799,411 S	10/2017	Dixon et al.
D815,590 S	4/2018	Kagimoto

* cited by examiner




Fig. 1




Fig. 2




Fig. 3




Fig. 4