



US00D885490S

(12) **United States Design Patent** (10) **Patent No.:** **US D885,490 S**
Sakai (45) **Date of Patent:** **** May 26, 2020**

(54) **TOY BEAD**

(71) Applicant: **EPOCH COMPANY LTD**

(72) Inventor: **Ryo Sakai**, Tokyo (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/681,194**

(22) Filed: **Feb. 22, 2019**

(30) **Foreign Application Priority Data**

Aug. 24, 2018 (JP) 2018-018464

(51) **LOC (12) Cl.** **21-01**

(52) **U.S. Cl.**

USPC **D21/398**; D21/484; D11/90; D11/125

(58) **Field of Classification Search**

USPC D21/398, 404, 468, 471, 478, 479, 484, D21/493, 498, 499, 504, 505, 386, 372, D21/373, 707, 714, 469, 496; D11/70, D11/76, 86, 88, 90, 124, 125, 142, 131, D11/157; D25/113; D26/4, 130, 134, D26/154; D19/59, 62, 101; D1/100, D1/106, 126, 127, 128, 199; 63/32, 38, 63/39; 52/DIG. 10; 428/11; 446/85, 446/106, 109, 488, 491, 87, 146, 92, 129, 446/137, 138, 108, 111-128; 434/208, 434/211, 393, 403, 96; 273/153 R, 156, 273/157 R, 160

CPC A63H 33/00; A63H 33/04; A63H 33/046; A63H 33/06; A63H 33/062; A63H 33/16; A63H 33/001; A63H 33/14; A63H 33/22; A63F 9/06; A63F 2009/0282; A63F 2009/0415; A63F 2009/0462; A63F 2009/0464; A63F 2009/1212; A63F 2009/1228; A63F 2009/1232; A63F 2250/505; A63F 2250/50; A63F 2003/00794; A44C 17/00; A44C 17/001; A44C 17/007; A44C 13/00; A47G 33/08; A47G 2033/0827; B44C 3/12

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D23,086 S *	2/1894	Porter	D21/493
D192,096 S *	1/1962	Pelzman	D11/90
3,461,574 A *	8/1969	Larsen	A63F 9/06
				434/403
D232,571 S *	8/1974	Coffin	D21/479
D236,996 S *	9/1975	Kennedy	D21/479
4,492,723 A *	1/1985	Chadwick, II	A63H 33/16
				428/11
4,976,652 A *	12/1990	Schwartz	A63H 33/04
				273/157 R
5,489,230 A *	2/1996	Gavula, Jr.	A63H 33/16
				428/33

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0084804 A1 *	8/1983	A44C 17/001
GB	2498410 A *	7/2013	B44C 3/12
JP	6047797 B *	6/1994		

Primary Examiner — Catherine A Tuttle


(57) **CLAIM**

The ornamental design for a toy bead, as shown and described.

DESCRIPTION

FIG. 1 is a perspective view of a toy bead showing my new design;
FIG. 2 is a front elevational view thereof;
FIG. 3 is a top plan view thereof;
FIG. 4 is a right side elevational view thereof;
FIG. 5 is a top and right view seen in the direction of arrow 5 in FIG. 3;
FIG. 6 is a rear elevational view thereof;
FIG. 7 is a bottom plan view thereof; and,
FIG. 8 is a left side elevation view thereof.

1 Claim, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,070,373 A * 6/2000 Diamond E04B 1/19
52/81.1
D510,294 S * 10/2005 Andersson D11/125
2006/0234600 A1 * 10/2006 Pacheco A63H 33/046
446/124
2012/0148810 A1 * 6/2012 Chen B44C 1/28
428/195.1
2018/0036647 A1 * 2/2018 Sakai A63H 33/04
2019/0192961 A1 * 6/2019 Sakai B44C 3/12

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

