



US00D886822S

(12) **United States Design Patent**  
**Mitchell**

(10) **Patent No.:** **US D886,822 S**  
(45) **Date of Patent:** **\*\* Jun. 9, 2020**

(54) **COORDINATE INPUT INSTRUMENT**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **Wacom Co., Ltd.**, Kazo-shi, Saitama (JP)

JP D1267831 S 4/2006  
KR D3009049120000 S 4/2017

(72) Inventor: **Giles Thomas Mitchell**, Setagaya-ku (JP)

OTHER PUBLICATIONS

(73) Assignee: **Wacom Co., Ltd.**, Kazo-shi (JP)

“Wacom Pro Pen 2 With Pen Case,” Wacom, <<https://us-store.wacom.com/Catalog/Accessories/wacom-pro-pen-2-with-case>> [retrieved May 10, 2018], 1 page.

(\*\*) Term: **15 Years**

*Primary Examiner* — Austin Murphy

(21) Appl. No.: **29/635,858**

(74) *Attorney, Agent, or Firm* — Christensen O’Connor Johnson Kindness PLLC

(22) Filed: **Feb. 2, 2018**

(30) **Foreign Application Priority Data**

Aug. 2, 2017 (JP) ..... 2017-016705

(51) **LOC (12) Cl.** ..... **14-02**

(52) **U.S. Cl.**  
USPC ..... **D14/411**

(58) **Field of Classification Search**

USPC ..... D14/372, 496, 432, 371, 125, 126, 129, D14/299, 411; D16/300–342; 351/158, 351/153, 144; 345/7–9, 905; 455/344; 348/115, 53, 121, 739  
CPC ..... G02B 27/017; G06F 3/016; G06F 3/033; G06F 3/0317; G06F 3/03545; G06F 3/041; G06K 9/222

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D527,050 S 8/2006 Hirota  
D584,772 S 1/2009 Hackenberg et al.  
D614,622 S 4/2010 Nakata  
D614,623 S 4/2010 Crisp et al.  
D617,327 S 6/2010 Crisp  
D670,700 S 11/2012 Halsinger et al.  
D699,723 S 2/2014 Nishizawa  
D744,484 S 12/2015 Huebner  
D750,630 S \* 3/2016 Nishizawa ..... D14/411  
D773,456 S 12/2016 Mitchell

(Continued)


(57) **CLAIM**

The ornamental design for a coordinate input instrument, as shown and described.

**DESCRIPTION**

FIG. 1 is a partially exploded top-front-right perspective view of a coordinate input instrument; FIG. 2 is a bottom-rear-left perspective view thereof; FIG. 3 is a bottom plan view thereof; FIG. 4 is a top plan view thereof; FIG. 5 is a right side elevational view thereof, wherein the left side elevational view is a mirror image of the right side elevational view; FIG. 6 is a front elevational view thereof; FIG. 7 is a view indicated by the view indicators shown in FIG. 6; and, FIG. 8 is a bottom-rear-left perspective view of the coordinate input instrument, wherein a cap is removed from the instrument, and replacement tips are stored in the instrument. The dashed broken lines in the drawings show portions of the coordinate input instrument that form no part of the claimed design.

**1 Claim, 4 Drawing Sheets**




(56)

**References Cited**


U.S. PATENT DOCUMENTS

D773,462 S	*	12/2016	Mitchell .....	D14/411
D781,859 S	*	3/2017	Magi .....	D14/411
D797,742 S	*	9/2017	Chang .....	D14/411
D799,488 S	*	10/2017	Nishizawa .....	D14/411
D848,425 S	*	5/2019	Lam .....	D14/411
D848,426 S	*	5/2019	Nishizawa .....	D14/411
D851,643 S	*	6/2019	Nishizawa .....	D14/411
D860,204 S	*	9/2019	Huebner .....	D14/411

\* cited by examiner




**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**




**FIG. 5**



**FIG. 6**



**FIG. 7**



**FIG. 8**