

US00D889224S

(12) **United States Design Patent** (10) **Patent No.:** **US D889,224 S**  
**Kukucka et al.** (45) **Date of Patent:** **\*\* Jul. 7, 2020**

(54) **EQUAL TORQUE HEX BIT** 8,448,547 B2 \* 5/2013 Whitehead ..... B25B 27/18  
81/441  
(71) Applicant: **GRIP HOLDINGS LLC**, Brandon, FL D769,690 S \* 10/2016 Campbell, II ..... F16B 23/003  
(US) D8/86  
D776,505 S \* 1/2017 Doroslovac ..... D8/29  
(72) Inventors: **Paul Kukucka**, Brandon, FL (US); D784,106 S \* 4/2017 Doroslovac ..... D8/86  
**Thomas Stefan Kukucka**, Brandon, FL D794,405 S \* 8/2017 Doroslovac ..... D8/29  
(US) D827,406 S \* 9/2018 Su ..... D8/86  
D829,069 S \* 9/2018 Doroslovac ..... D8/29  
(73) Assignee: **GRIP HOLDINGS LLC**, Brandon, FL 10,081,094 B2 \* 9/2018 Doroslovac ..... B25B 15/001  
(US) 10,100,864 B2 \* 10/2018 Rathmann ..... F16B 23/003  
D833,247 S \* 11/2018 Huang ..... D8/86  
D845,484 S \* 4/2019 Bilodeau ..... D24/152  
D859,944 S 9/2019 Kukucka  
D859,945 S \* 9/2019 Kukucka ..... D8/29

(Continued)

(21) Appl. No.: **29/718,215**

(22) Filed: **Dec. 20, 2019**

(51) **LOC (12) Cl.** ..... **08-05**

(52) **U.S. Cl.**  
USPC ..... **D8/29; D8/86**

(58) **Field of Classification Search**  
USPC ..... D8/29, 86; D15/138  
CPC ..... B25B 13/06; B25B 13/065  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D53,641 S \* 7/1919 Rosel ..... D8/28  
D111,026 S \* 8/1938 Hosford ..... D8/26  
D217,896 S \* 6/1970 Sexauer ..... D8/29  
5,207,132 A \* 5/1993 Goss ..... B25B 13/065  
81/460  
D410,367 S \* 6/1999 Applegate ..... D21/789  
6,314,846 B1 \* 11/2001 Winick ..... B25B 23/142  
81/477  
D522,821 S \* 6/2006 Hsieh ..... D8/29  
7,168,348 B2 1/2007 Holland-Letz  
7,225,710 B2 6/2007 Pacheco, Jr.  
7,413,693 B2 \* 8/2008 Goacher, Sr. .... B25B 13/5091  
264/148  
D614,931 S \* 5/2010 Su ..... D8/86

FOREIGN PATENT DOCUMENTS

WO 2018150360 8/2018

*Primary Examiner* — Patricia A Palasik


(57) **CLAIM**

The ornamental design for an equal torque hex bit, as shown and described.

**DESCRIPTION**

FIG. 1 is a top perspective view of an equal torque hex bit showing my new design;  
FIG. 2 is a bottom perspective view thereof;  
FIG. 3 is a front elevated view thereof;  
FIG. 4 is a rear elevated view thereof;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof;  
FIG. 7 is a right elevated view thereof; and,  
FIG. 8 is a left elevated view thereof.  
The broken lines showing of a hole in FIG. 1-8, and the broken lines showing of a bit body in FIG. 1-8 are included for the purpose of showing environmental structure and form no part of the claimed design.

**1 Claim, 8 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

10,428,859 B2 \* 10/2019 Falkenstein ..... F16B 23/003  
2016/0059391 A1 \* 3/2016 Hettich ..... B25B 15/005  
81/460

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8