



US00D891515S

(12) **United States Design Patent**  
**Sakai**

(10) **Patent No.:** **US D891,515 S**

(45) **Date of Patent:** **\*\* Jul. 28, 2020**

(54) **BEAD RECEIVER**

(71) Applicant: **EPOCH COMPANY, LTD**, Taito-ku,  
Tokyo (JP)

(72) Inventor: **Ryo Sakai**, Tokyo (JP)

(73) Assignee: **EPOCH COMPANY, LTD.**, Tokyo  
(JP)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/671,863**

(22) Filed: **Nov. 30, 2018**

(51) **LOC (12) Cl.** ..... **19-06**

(52) **U.S. Cl.**  
USPC ..... **D19/111**

(58) **Field of Classification Search**  
USPC ..... D19/108, 111, 113, 114; D7/552.1, 698;  
D21/469  
CPC ..... A63H 33/00; A63H 33/06; A63H 33/08;  
A63H 33/086; A63H 33/088; A63H  
33/001; A63H 33/14; A63F 9/06; B44C  
3/00; B44C 3/12; B44C 3/123; G09F  
9/37

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

- 2,923,452 A \* 2/1960 Holovka, Jr. .... G06K 19/00  
225/93
- D222,882 S \* 1/1972 Sharer ..... D19/113
- 4,246,702 A \* 1/1981 Burt ..... B43L 13/201  
33/27.11
- 4,986,756 A \* 1/1991 Yamaguchi ..... A63F 9/06  
273/157 R
- D344,975 S \* 3/1994 Tarozzi ..... D19/113
- 5,704,789 A \* 1/1998 Yang ..... B44C 3/123  
221/185
- D434,606 S \* 12/2000 Reames ..... D7/552.1
- D502,031 S \* 2/2005 Cassidy ..... D20/40

- D530,371 S \* 10/2006 Balzer ..... D19/111
- 7,340,994 B2 \* 3/2008 Bruno ..... A47J 37/067  
99/426
- 7,390,237 B2 \* 6/2008 Lin ..... A63F 9/06  
273/282.1
- 7,677,564 B2 \* 3/2010 Kriger ..... A63F 3/0415  
273/148 R
- D656,789 S \* 4/2012 Locke ..... D7/541
- D688,084 S \* 8/2013 Henry ..... D7/354
- 8,827,711 B2 \* 9/2014 Davis, II ..... G09F 5/02  
434/96
- 9,320,330 B2 \* 4/2016 Cooke ..... A63F 9/06
- D767,933 S \* 10/2016 Lee ..... D7/352
- 9,956,495 B2 \* 5/2018 Kamiyama ..... A63F 9/06
- 10,328,356 B1 \* 6/2019 Harper ..... B44B 9/00

(Continued)

*Primary Examiner* — Elizabeth A. Albert

(74) *Attorney, Agent, or Firm* — Fitzgerald IP Law; John  
K. Fitzgerald, Esq.


(57) **CLAIM**

The ornamental design for a bead receiver, as shown and  
described.

**DESCRIPTION**

FIG. 1 is a perspective view of a front, bottom and right side  
of a bead receiver showing my new design;  
FIG. 2 is a perspective view of the rear, top and left side  
thereof;  
FIG. 3 is a front view thereof;  
FIG. 4 is a rear view thereof;  
FIG. 5 is a top plan view thereof;  
FIG. 6 is a bottom plan view thereof;  
FIG. 7 is a right side view thereof;  
FIG. 8 is a left side view thereof;  
FIG. 9 is another front perspective view thereof; and,  
FIG. 10 is still another rear perspective view thereof.  
The broken lines shown are included for the purpose of  
illustrating portions of the article which form no part of the  
claimed design.

**1 Claim, 10 Drawing Sheets**



(56)

**References Cited**


U.S. PATENT DOCUMENTS

10,478,740 B2 \* 11/2019 Sakai ..... A63H 33/001  
2002/0102905 A1 \* 8/2002 Tseng ..... A63H 33/26  
446/131  
2005/0239038 A1 \* 10/2005 Olsen ..... G09B 11/04  
434/409  
2010/0018409 A1 \* 1/2010 Snyder ..... A21B 3/15  
99/324  
2016/0354705 A1 \* 12/2016 Poulus ..... A63H 33/086  
2018/0161689 A1 \* 6/2018 Kislevitz ..... A63H 33/105  
2019/0223573 A1 \* 7/2019 Maroun ..... A45D 44/00  
2020/0094131 A1 \* 3/2020 Sakai ..... A63F 9/06

\* cited by examiner




**FIG. 1**






**FIG. 2**






**FIG. 3**






*FIG. 4*






*FIG. 5*



*FIG. 6*





***FIG. 7***




*FIG. 8*





**FIG. 9**





**FIG. 10**

