



US00D892779S

(12) **United States Design Patent**
Huang

(10) **Patent No.:** **US D892,779 S**
(45) **Date of Patent:** **** Aug. 11, 2020**

(54) **WIRELESS SIGNAL TRANSMISSION
DEVICE ASSEMBLY**

(71) Applicant: **Wistron NeWeb Corp.**, Hsinchu (TW)

(72) Inventor: **Bau-Yi Huang**, Hsinchu (TW)

(73) Assignee: **WISTRON NEWEB CORP**, Hsinchu
(TW)

(**) Term: **15 Years**

(21) Appl. No.: **29/731,482**

(22) Filed: **Apr. 15, 2020**

Related U.S. Application Data

(62) Division of application No. 29/676,195, filed on Jan. 9, 2019, now Pat. No. Des. 884,687.

(51) **LOC (12) Cl.** **14-03**

(52) **U.S. Cl.**
USPC **D14/240; D14/358**

(58) **Field of Classification Search**

USPC ... D14/140.1, 240, 242, 358, 125, 129, 130,
D14/140, 142, 155, 167, 168, 172, 188,
D14/195, 203.1, 203.6, 299, 496, 348,
D14/351, 356, 357, 197, 198, 230, 104.6,
D14/434, 447, 217, 224, 238; D13/123,
D13/152, 158, 162, 162.1, 163, 168, 184,
D13/199; D10/104.1, 106.1, 106.6,
D10/116.1, 61, 64, 75, 106.9
CPC ... H04W 88/00; H04W 88/005; H04W 88/02;
H04W 88/08; H04W 88/085; H04W
88/12; H04W 88/14; H04W 88/16; H04W
88/18; H04W 4/00; H01Q 1/02; H01Q
1/2291; H01Q 1/246; H04B 1/38
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D455,735 S 4/2002 Winslow
D476,337 S * 6/2003 Bradley D14/434

D478,057 S 8/2003 Cohen et al.
D493,447 S 7/2004 Noro et al.
D549,119 S 8/2007 Becker
D550,659 S 9/2007 Nora
D565,035 S 3/2008 Takisawa
D575,280 S 8/2008 Marquez

(Continued)

OTHER PUBLICATIONS

Transmitting radio signals devices. (Design—© Questel) orbit.com.
[online PDF]25 pgs. Print Dates Oct. 25, 2019. [retrieved Mar. 16,
2020] <https://www.orbit.com/export/QPTUJ214/pdf2/7b8a3d71-b505-4032-ad41-12215f9a78ee-165209.pdf>.

Primary Examiner — Marie D. Fast Horse

(74) *Attorney, Agent, or Firm* — McClure, Qualey &
Rodack, LLP


(57) **CLAIM**

The ornamental design for a wireless signal transmission device assembly, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a wireless signal transmission device assembly in accordance with my new design, wherein the wireless signal transmission device includes a holder and two wireless signal transmission devices disposed on the holder;
FIG. 2 is a rear perspective view thereof;
FIG. 3 is a front view thereof;
FIG. 4 is a rear view thereof;
FIG. 5 is a left view thereof;
FIG. 6 is a right view thereof;
FIG. 7 is a top plan view thereof; and,
FIG. 8 is a bottom plan view thereof.
The broken lines depict portions of the wireless signal transmission device assembly that form no part of the claimed design.

1 Claim, 8 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D577,708	S	9/2008	von Meiss et al.	
7,791,558	B2	9/2010	Su et al.	
D638,425	S	5/2011	Ikeda et al.	
D682,200	S *	5/2013	Rautiainen	D13/108
D706,249	S	6/2014	Holzer	
D707,627	S	6/2014	Brunner et al.	
D707,666	S	6/2014	Ting et al.	
D722,023	S	2/2015	Brunner et al.	
D722,964	S *	2/2015	Regole	D13/103
D732,530	S	6/2015	Hermansson et al.	
D739,849	S	9/2015	Donohue, II et al.	
D766,214	S	9/2016	Mackiewicz et al.	
D816,520	S	5/2018	Elrod et al.	
D819,619	S	6/2018	Li	
D834,569	S	11/2018	Moon	
D843,359	S	3/2019	Moon	
D852,791	S	7/2019	Sohn et al.	
D874,536	S *	2/2020	Park	D10/104.1
D879,078	S *	3/2020	Boggs	D14/240
D883,965	S *	5/2020	Huang	D14/240
D884,687	S *	5/2020	Huang	D14/240

* cited by examiner




FIG. 1




FIG. 2



FIG. 3



FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8