



US00D893029S

(12) **United States Design Patent** (10) **Patent No.:** **US D893,029 S**
Qun (45) **Date of Patent:** **** Aug. 11, 2020**

(54) **ULTRASONIC CUTTER HEAD**
(71) Applicant: **BEIJING SMTP TECHNOLOGY CO., LTD.**, Beijing (CN)
(72) Inventor: **Cao Qun**, Beijing (CN)
(73) Assignee: **BEIJING SMTP TECHNOLOGY CO., LTD.**, Beijing (CN)
(**) Term: **15 Years**
(21) Appl. No.: **29/635,570**
(22) Filed: **Jan. 31, 2018**
(51) **LOC (12) Cl.** **24-02**
(52) **U.S. Cl.**
USPC **D24/146**
(58) **Field of Classification Search**
USPC D24/108, 133, 150, 152, 155, 176, 210, D24/231, 216, 232, 185, 186, 104, D24/112-114, 117-119, 127, 141, 144, D24/188, 207, 200, 209, 215, 171; D15/21, 22, 23, 24, 25, 26, 27, 28, 29, D15/138, 139, 140; D8/70, 95, 96, 98; D25/126; D28/7, 9, 20
CPC B23B 51/02; B23B 51/08; B23B 51/10; B23B 51/00; B23B 2251/50; B23B 2251/18; B23B 2251/46; B23B 2222/28; B23B 2240/08; Y10S 408/713; Y10T 407/26; Y10T 408/9097; Y10T 408/899; Y10T 408/90; A61C 3/02; A61C 8/0089; A61C 1/07; A61B 17/3213; A61B 17/3417; A61B 17/14; A61B 17/142; A61B 17/320016; A61B 17/32002; A61B 17/3211; A61B 2017/00473; A61B 2017/320032; A61B 2017/32113; A61B 2017/32116; A61B 2017/3454; A61B 2018/1412; A61B 90/30; A61B 17/1615; A61B 17/162; A61B 17/1624; A61B 17/1633; A61B 17/1637; A61B 17/1659; A61B 17/16; A61B 17/1604; A61B 17/144; A61B 2017/00261; A61B

2017/320075; A61B 2017/32007; A61B 2017/320077; A61B 2217/007; A61B 17/1642; A61B 17/1671; B23D 77/02; B23D 61/006; B23D 61/121; B23P 15/32; B27B 19/006
See application file for complete search history.


(56) **References Cited**
U.S. PATENT DOCUMENTS
D341,202 S * 11/1993 Hood D24/133
D619,714 S * 7/2010 Kim D24/146
D737,444 S * 8/2015 Mueller D24/147
2007/0029459 A1 * 2/2007 Hanson E04H 12/2215
248/530
2008/0208320 A1 * 8/2008 Tan-Malecki A61B 17/1617
623/1.17

(Continued)
Primary Examiner — Samantha Q Lawrence
(74) *Attorney, Agent, or Firm* — Maschoff Brennan

(57) **CLAIM**
The ornamental design for an ultrasonic cutter head, as shown and described.

DESCRIPTION
FIG. 1 is a top, front, and left side perspective view of an ultrasonic cutter head, showing our new design;
FIG. 2 is a top plan view thereof;
FIG. 3 is a left side view thereof;
FIG. 4 is a right side view thereof;
FIG. 5 is a bottom plan view thereof;
FIG. 6 is a front elevational view thereof;
FIG. 7 is a rear elevational view thereof; and,
FIG. 8 is a full view thereof.
The broken lines shown in FIGS. 1-5 and 7-8 atop the cylinder illustrate boundaries of the ultrasonic cutter head. The additional broken lines shown in FIG. 8 illustrate environment and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0112563 A1* 5/2011 To A61B 17/32078
606/159
2016/0135820 A1* 5/2016 Lechot A61B 17/1615
606/81
2017/0035443 A1* 2/2017 Sausen A61B 17/1642
2019/0143414 A1* 5/2019 Vayser A61B 1/32
2019/0143418 A1* 5/2019 Su B23B 5/167
408/229
2019/0307323 A1* 10/2019 Claude A61B 1/00082
2019/0328429 A1* 10/2019 McCormack A61B 17/8822

* cited by examiner




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8