



US00D896166S

(12) **United States Design Patent**  
**Yamaoka**

(10) **Patent No.:** **US D896,166 S**

(45) **Date of Patent:** **\*\* Sep. 15, 2020**

- (54) **TIRE FOR AUTOMOBILE**
- (71) Applicant: **SUMITOMO RUBBER INDUSTRIES, LTD.**, Kobe-shi, Hyogo (JP)
- (72) Inventor: **Hiroshi Yamaoka**, Kobe (JP)
- (73) Assignee: **SUMITOMO RUBBER INDUSTRIES, LTD.**, Kobe-Shi, Hyogo (JP)

D791,067 S *	7/2017	Iwabuchi	.....	D12/605
D791,693 S *	7/2017	Iwabuchi	.....	D12/605
D795,798 S *	8/2017	Kamada	.....	D12/605
D803,149 S *	11/2017	Ishikawa	.....	D12/605
D804,402 S *	12/2017	Kamada	.....	D12/605
D807,284 S *	1/2018	Iwabuchi	.....	D12/605
D808,333 S *	1/2018	Iwabuchi	.....	D12/605
D813,799 S *	3/2018	Maxwell	.....	D12/605
D814,395 S *	4/2018	Sano	.....	D12/605
D817,860 S *	5/2018	Maxwell	.....	D12/605
D823,785 S *	7/2018	Noel	.....	D12/605
D843,930 S *	3/2019	Itoi	.....	D12/605
D848,358 S *	5/2019	Kamada	.....	D12/605

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/692,838**

(22) Filed: **May 29, 2019**

(51) **LOC (12) Cl.** ..... **12-15**

(52) **U.S. Cl.**  
USPC ..... **D12/605**

(58) **Field of Classification Search**  
USPC ..... D12/604, 605  
CPC ..... B60C 13/00; B60C 1/00  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

D588,532 S *	3/2009	Shondel	.....	D12/605
D590,332 S *	4/2009	Sato	.....	D12/605
D593,486 S *	6/2009	Yonetsu	.....	D12/605
D618,165 S *	6/2010	Sato	.....	D12/605
D666,143 S *	8/2012	Sato	.....	D12/605
D693,761 S *	11/2013	Nakamura	.....	D12/605
D769,806 S *	10/2016	Yasunaga	.....	D12/605
D769,807 S *	10/2016	Ishikawa	.....	D12/605
D773,986 S *	12/2016	Nakamura	.....	D12/605
D777,656 S *	1/2017	Maxwell	.....	D12/605
D777,658 S *	1/2017	Taniguchi	.....	D12/605
D790,450 S *	6/2017	Sato	.....	D12/605
D790,451 S *	6/2017	Sato	.....	D12/605

\* cited by examiner

*Primary Examiner* — Michelle E. Wilson

*Assistant Examiner* — Clese Moore, Jr.

(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(57) **CLAIM**

The ornamental design for a tire for automobile, as shown and described.

**DESCRIPTION**

FIG. 1 is a front view of a tire for automobile showing my new design;

FIG. 2 is a rear view thereof;

FIG. 3 is a top view thereof;

FIG. 4 is a bottom view thereof;

FIG. 5 is a right view thereof;


FIG. 6 is a left view thereof;

FIG. 7 is a partially enlarged view of a portion defined by lines 7-7 shown in FIG. 1; and,

FIG. 8 is a cross-sectional view taken in direction of line 8-8 in FIG. 7.

The portions shown in broken lines illustrate the boundary of the design and form no part of the claimed design.

**1 Claim, 8 Drawing Sheets**






FIG. 1




FIG. 2



FIG. 3



FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8