



US00D897818S

(12)

United States Design Patent

Tien

(10) Patent No.:

US D897,818 S

(45) Date of Patent:

** Oct. 6, 2020

(54) LATCH COUPLING DEVICE

(71) Applicant: I-TEK METAL MFG. CO., LTD.,
Tainan (TW)

(72) Inventor: Hung-Jen Tien, Tainan (TW)

(73) Assignee: I-TEK METAL MFG. CO., LTD.,
Tainan (TW)

(**) Term: 15 Years

(21) Appl. No.: 29/672,511

(22) Filed: Dec. 6, 2018

(51) LOC (12) Cl. 08-07

(52) U.S. Cl.
USPC D8/331

(58) Field of Classification Search
USPC D8/330, 331, 336, 338, 339, 341, 342,
D8/343, 344, 349, 382
CPC E05B 15/02; E05B 15/0205; E05B 5/00;
E05B 9/00; E05B 45/08; E05B 45/083;
E05B 65/0007; Y10T 292/53; Y10T
292/68; Y10T 292/0803; Y10T 292/0813;
Y10T 292/0848; Y10T 70/5199
See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,357,552	A *	9/1944	Schlage	E05B 9/00 292/337
4,065,162	A *	12/1977	Schlage	E05B 15/0205 292/340
4,186,954	A *	2/1980	Detlefs	E05B 15/0205 292/340
D259,856	S *	7/1981	Ciener	292/346
D261,225	S *	10/1981	Sterling	292/340
D261,478	S *	10/1981	Gauntt	292/340
D263,675	S *	4/1982	Vorves	292/340
D273,937	S *	5/1984	Ruff	D8/344
D283,299	S *	4/1986	Mazie	292/340
D302,937	S *	8/1989	Briggs	D8/344

D303,351	S *	9/1989	Weinerman	D8/344
D303,754	S *	10/1989	Weinerman	D8/344
D305,403	S *	1/1990	Johnson	D8/344
D314,131	S *	1/1991	Russell	D8/300
D319,964	S *	9/1991	Johns	D8/344
5,171,050	A *	12/1992	Mascotte	E05B 15/025 292/340
D339,056	S *	9/1993	Black	D8/344
5,257,841	A *	11/1993	Geringer	E05B 45/083 292/340
D351,781	S *	10/1994	DeWitt	D8/343
D393,794	S *	4/1998	Blanch	D8/344
D452,811	S *	1/2002	Shedd	D8/344
D461,700	S *	8/2002	Meredith	D8/344

(Continued)

OTHER PUBLICATIONS

Von Duprin Strike 264, door hardware, rbadoor.com, https://www.rbadoor.com/von-duprin-strike-264.html?gclid=EAlaQobChMl7Nnm8i15wIVyJ-zCh2MMAdfEAQYBSABEgl1H_D_BwE.*

Primary Examiner — Steven J Czyz
(74) Attorney, Agent, or Firm — Alan D. Kamrath; Karin L. Williams; Mayer & Williams PC


(57) CLAIM

The ornamental design for a latch coupling device, as shown and described.

DESCRIPTION

FIG. 1 is a front, perspective view of a latch coupling device showing my design;
FIG. 2 is a rear, perspective view thereof;
FIG. 3 is a front elevational view thereof;
FIG. 4 is a rear elevational view thereof;
FIG. 5 is a left elevational view thereof;
FIG. 6 is a right elevational view thereof;
FIG. 7 is a top plan view thereof; and,
FIG. 8 is a bottom plan view thereof.

1 Claim, 8 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D525,859 S	*	8/2006	Eichert	D8/344
D664,421 S	*	7/2012	Bishir	D8/331
D697,386 S	*	1/2014	Dooley	D8/343
D707,102 S	*	6/2014	Hale	D8/331
9,016,736 B1	*	4/2015	Anderson	E05B 15/0205
				292/288
9,422,742 B2	*	8/2016	Pardoe	E05B 15/0205
D768,465 S	*	10/2016	Strydom	D8/331
D777,558 S	*	1/2017	Magee	E05B 15/025
				D8/344
D791,575 S	*	7/2017	Hochman	D8/330
D846,367 S	*	4/2019	Romero, Jr.	D8/343

* cited by examiner




FIG.1




FIG.2




FIG.3




FIG.4




FIG.5




FIG.6




FIG.7




FIG.8