

US00D899854S

(12) **United States Design Patent** (10) **Patent No.:** **US D899,854 S**
Jacob (45) **Date of Patent:** **** Oct. 27, 2020**

- (54) **BEVERAGE SYSTEM**
- (71) Applicant: **BruMate, LLC**, Denver, CO (US)
- (72) Inventor: **Dylan M. Jacob**, Denver, CO (US)
- (73) Assignee: **BruMate, LLC**, Denver, CO (US)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/675,424**
- (22) Filed: **Jan. 1, 2019**

Related U.S. Application Data


- (62) Division of application No. 29/594,947, filed on Feb. 23, 2017, now Pat. No. Des. 836,983.
- (51) **LOC (12) Cl.** **07-01**
- (52) **U.S. Cl.**
USPC **D7/507; D7/532; D7/602**
- (58) **Field of Classification Search**
USPC D7/505, 507, 509-511, 523, 527, 529,
D7/531, 532, 300.1, 591, 608, 392.1,
D7/396.2, 624.1, 624.2, 602, 601;
D9/530, 504, 538, 501; 220/200, 592.16,
220/592.17
CPC A47G 19/22; A47G 19/2205; A47G
19/2227; A45F 3/16; A47J 43/27
See application file for complete search history.

D548,086	S	*	8/2007	Conway	D7/300.1
D551,984	S		10/2007	La Kier et al.		
D557,140	S		12/2007	Voight et al.		
D591,556	S		5/2009	Fuller		
D602,362	S		10/2009	Hering		
7,628,285	B2		12/2009	Salvia		
D635,019	S		3/2011	Goto et al.		
D641,591	S		7/2011	Tsukida		
8,033,407	B2	*	10/2011	Minca	A47J 41/0072 215/11.6
D654,762	S		2/2012	Gilbert		
D660,084	S		5/2012	Gilbert		
D664,045	S		7/2012	Toh et al.		
D689,331	S	*	9/2013	Staton	D7/510
D690,988	S		10/2013	Audette		
D707,087	S		6/2014	Joy		
D727,093	S		4/2015	Lapsker		
D727,688	S		4/2015	Hewitt et al.		
D728,314	S		5/2015	Carstensen et al.		
D729,581	S	*	5/2015	Boroski	D7/510
D732,968	S		6/2015	Heisner et al.		
D750,497	S		3/2016	Gibbs et al.		
D752,397	S		3/2016	Seiders et al.		
D761,618	S		7/2016	Lapsker		
D761,623	S		7/2016	Leimone		
D761,624	S	*	7/2016	McLean	D7/507
D770,851	S		11/2016	Herbst		
D773,296	S		12/2016	Lynd et al.		
D775,495	S		1/2017	Boroski et al.		
D779,285	S		2/2017	Seiders et al.		
D779,891	S		2/2017	Seiders et al.		
D779,892	S		2/2017	Seiders et al.		
D780,530	S	*	3/2017	Seiders	D7/624.2
D780,531	S		3/2017	Seiders et al.		
D780,532	S		3/2017	Seiders et al.		
D780,533	S		3/2017	Seiders et al.		
D784,763	S		4/2017	Oshana		
D786,025	S		5/2017	Seiders et al.		
D786,700	S		5/2017	Schlatter et al.		
D795,012	S	*	8/2017	Rummel	D7/510
D799,901	S	*	10/2017	Jacob	D7/510
D800,501	S	*	10/2017	Rummel	D7/509
D810,511	S	*	2/2018	Harrington, III	D7/511
D819,406	S	*	6/2018	Rivera	D7/532
D820,045	S	*	6/2018	Harrington, III	D7/511
10,005,608	B1		6/2018	Jacob		
D824,212	S	*	7/2018	Seiders	D7/396.2
D826,003	S		8/2018	Seiders et al.		
D829,058	S		9/2018	Seiders et al.		
D836,983	S	*	1/2019	Jacob	D7/510
D842,028	S	*	3/2019	Melanson	D7/392.1
D861,433	S	*	10/2019	Busch	D7/509
D862,235	S	*	10/2019	Sanghavi	D9/529

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,212,963	A	5/1993	McGinnis	
D373,704	S	9/1996	Doxey	
D398,479	S	9/1998	Vultaggio et al.	
D416,198	S	11/1999	Lindsay	
D445,339	S	* 7/2001	Bazlur D9/538
D492,546	S	7/2004	Bodum	
D501,362	S	2/2005	Gauss	
D507,971	S	* 8/2005	Harris D9/516
D534,762	S	1/2007	Gluck	
D539,155	S	3/2007	Steinmann	
D539,567	S	3/2007	Webb et al.	
D541,665	S	5/2007	Druart	



D863,888 S *	10/2019	Meyers	D7/413
2013/0126369 A1	5/2013	Gamelli		
2014/0205725 A1 *	7/2014	Albanese	A47J 31/20 426/433
2014/0251938 A1	9/2014	Rose		
2017/0121074 A1 *	5/2017	Seiders	B65D 51/1605

OTHER PUBLICATIONS

https://www.amazon.com/KelvZ-Insulated-Stainless-Cooler-Holder/dp/B01LZ44Y4X/ref=sr_1_46?dchild=1&keywords=can+holder&qid=1592418448&sr=8-46 (Year: 2016).*

https://www.amazon.com/BrüMate-HOPSULATOR-Stainless-Insulated-Cooler/dp/B076H9C2LL/ref=psdc_678543011_t1_B07XTHVMDR (Year: 2017).*

* cited by examiner

Primary Examiner — Jae Liang
(74) *Attorney, Agent, or Firm* — Reichel Stohry Dean LLP; Mark C. Reichel; Natalie J. Dean

(57) **CLAIM**

The ornamental design for a beverage system, as shown and described.

DESCRIPTION

FIG. 1 is an exploded perspective view of a first embodiment of a beverage system showing our new design;
FIG. 2 is a top view of the lid portion shown in FIG. 1, with the container portion, the flange portion, and the adapter portion removed for ease of illustration;
FIG. 3 is a side view of FIG. 2;
FIG. 4 is a bottom view of FIG. 2;
FIG. 5 is a second side view of FIG. 2;
FIG. 6 is a top view of the flange portion shown in FIG. 1, with the container portion, the lid portion, and the adapter portion removed for ease of illustration;
FIG. 7 is a side view of FIG. 6;
FIG. 8 is a bottom view of FIG. 6;
FIG. 9 is a second side view of FIG. 6;
FIG. 10 is a top view of the adapter portion shown in FIG. 1, with the container portion, the lid portion, and the flange portion removed for ease of illustration;
FIG. 11 is a side view of FIG. 10;
FIG. 12 is a bottom view of FIG. 10;
FIG. 13 is a second side view of FIG. 10;
FIG. 14 is a front view of the container portion shown in FIG. 1, with the lid portion, the flange portion, and the adapter portion removed for ease of illustration;
FIG. 15 is a rear view of FIG. 14;
FIG. 16 is a right side view of FIG. 14;
FIG. 17 is a left side view of FIG. 14;
FIG. 18 is a top view of FIG. 14;
FIG. 19 is a bottom view of FIG. 14;
FIG. 20 is a top view of FIG. 14, having the adapter portion positioned within the container portion, the adapter portion shown in a top view;
FIG. 21 is a front view of the container portion shown in FIG. 1, with the flange portion coupled to the container portion, the flange portion partially shown in a front view;
FIG. 22 is a rear view of FIG. 21;
FIG. 23 is a right side view of FIG. 21;

FIG. 24 is a left side view of FIG. 21;
FIG. 25 is a top view of FIG. 21;
FIG. 26 is a bottom view of FIG. 21;
FIG. 27 is a top view of FIG. 14, having the adapter portion positioned within the container portion, the adapter portion shown in a top view, and with the flange portion coupled to the container portion, the flange portion partially shown in a top view;
FIG. 28 is a front view of the container portion shown in FIG. 1, with the flange portion coupled to the container portion, the flange portion partially shown in a front view;
FIG. 29 is a rear view of FIG. 28;
FIG. 30 is a right side view of FIG. 28;
FIG. 31 is a left side view of FIG. 28;
FIG. 32 is a top view of FIG. 28; and
FIG. 33 is a bottom view of FIG. 28.
FIG. 34 is an exploded perspective view of a second embodiment of a beverage system showing our new design;
FIG. 35 is a top view of the flange portion shown in FIG. 34, with the container portion, the lid portion, and the adapter portion removed for ease of illustration;
FIG. 36 is a side view of FIG. 35;
FIG. 37 is a bottom view of FIG. 35;
FIG. 38 is a second side view of FIG. 35;
FIG. 39 is a top view of the adapter portion shown in FIG. 34, with the container portion, the lid portion, and the flange portion removed for ease of illustration;
FIG. 40 is a side view of FIG. 39;
FIG. 41 is a bottom view of FIG. 39;
FIG. 42 is a second side view of FIG. 39;
FIG. 43 is a front view of the container portion shown in FIG. 34, with the lid portion, the flange portion, and the adapter portion removed for ease of illustration;
FIG. 44 is a rear view of FIG. 43;
FIG. 45 is a right side view of FIG. 43;
FIG. 46 is a left side view of FIG. 43;
FIG. 47 is a top view of FIG. 43;
FIG. 48 is a bottom view of FIG. 43;
FIG. 49 is a top view of FIG. 43, having the adapter portion positioned within the container portion, the adapter portion shown in a top view;
FIG. 50 is a front view of the container portion shown in FIG. 34, with the flange portion coupled to the container portion, the flange portion partially shown in a front view;
FIG. 51 is a rear view of FIG. 50;
FIG. 52 is a right side view of FIG. 50;
FIG. 53 is a left side view of FIG. 50;
FIG. 54 is a top view of FIG. 50;
FIG. 55 is a bottom view of FIG. 50; and,
FIG. 56 is a top view of FIG. 43, having the adapter portion positioned within the container portion, the adapter portion shown in a top view, and with the flange portion coupled to the container portion, the flange portion partially shown in a top view.
The broken lines in the drawings depict portions of the beverage system that form no part of the claimed design.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56