



US00D900121S

(12) **United States Design Patent** (10) **Patent No.:** **US D900,121 S**
Pierson et al. (45) **Date of Patent:** **** Oct. 27, 2020**

(54) **POSITIONABLE GRIPPING DEVICE**
(71) Applicant: **Grip Curl, LLC**, Chandler, AZ (US)
(72) Inventors: **Derrick Pierson**, Chandler, AZ (US);
Charles Pierson, Chandler, AZ (US);
Aaron Bickel, Chandler, AZ (US)
(73) Assignee: **Grip Curl, LLC**, Chandler, AZ (US)
(**) Term: **15 Years**

D737,264 S * 8/2015 Shamsadov D14/251
D743,409 S * 11/2015 Chen D14/447
D749,083 S * 2/2016 Senoff D14/451
D756,368 S * 5/2016 Coleman D14/447
D765,549 S * 9/2016 Khodapanah D12/114
D765,662 S * 9/2016 Kang D14/251
9,560,186 B2 1/2017 Son et al.
D826,236 S * 8/2018 Chang D14/439
D826,947 S * 8/2018 Zhong D14/439
D830,367 S * 10/2018 Chang D14/440
D877,154 S * 3/2020 Hummel D14/447
D879,792 S * 3/2020 Glickstein D14/452

(Continued)

(21) Appl. No.: **29/717,351**

Primary Examiner — Angela J Lee

(22) Filed: **Dec. 17, 2019**

(74) Attorney, Agent, or Firm — The Noblitt Group,
PLLC

Related U.S. Application Data

(63) Continuation of application No. 16/382,595, filed on
Apr. 12, 2019, now Pat. No. 10,568,410.

(51) **LOC (12) Cl.** **08-07**

(52) **U.S. Cl.**
USPC **D14/447**

(58) **Field of Classification Search**
USPC D14/447, 432, 434, 439, 440, 451, 452,
D14/457, 239; D8/363, 373, 380;
D6/406.3, 406.4, 406.5, 406.6; D12/415
CPC A47B 21/04; A47B 2097/006; A47B
2097/005; A47B 2023/049; A45C
2011/002; A45C 2011/003; F16M
2200/00; F16M 13/00

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,020,527 A 5/1977 O'Neill
4,606,484 A 8/1986 Winter et al.
5,609,375 A 3/1997 Cohen
8,328,055 B1 12/2012 Snyder
8,374,657 B2 2/2013 Interdonato
8,690,210 B1 4/2014 May
D721,373 S * 1/2015 Logereau D14/432

(57) **CLAIM**

The ornamental design for a positional gripping device, as
shown and described.

DESCRIPTION

FIG. 1 is a front view of a positionable gripping device
showing the claimed design;

FIG. 2 is a back view of the positionable gripping device
shown in FIG. 1;

FIG. 3 is a perspective view of the positionable gripping
device shown in FIG. 1 with a gripping element in a first
position;


FIG. 4 is a perspective view of the positionable gripping
device shown in FIG. 1 with a gripping element in a second
position;

FIG. 5 is a side view of the positionable gripping device
shown in FIG. 1 with a gripping element in the first position;
and,

FIG. 6 is a side view of the positionable gripping device
shown in FIG. 1 with a gripping element in the second
position.

The broken lines in the figures form no part of the claimed
design.

1 Claim, 2 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0074291	A1	3/2012	Fu
2013/0295549	A1	11/2013	Hills
2015/0182009	A1	7/2015	Whang et al.
2016/0345695	A1	12/2016	Stagge
2019/0104623	A1	4/2019	Backus

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5




FIG. 6