



US00D905881S

(12) **United States Design Patent** (10) **Patent No.:** **US D905,881 S**
Katou (45) **Date of Patent:** **** Dec. 22, 2020**

(54) **REAR COMBINATION LAMP FOR AUTOMOBILE**

D565,211 S * 3/2008 Haller D26/28
D570,015 S * 5/2008 Hsu D26/28

* cited by examiner

(71) Applicant: **Nissan Motor Co., Ltd.**, Kanagawa (JP)

Primary Examiner — Marcus A Jackson

(72) Inventor: **Tadashi Katou**, Kanagawa (JP)

(74) *Attorney, Agent, or Firm* — Global IP Counselors, LLP

(73) Assignee: **Nissan Motor Co., Ltd.**, Yokohama (JP)

(57) **CLAIM**

The ornamental design for a rear combination lamp for an automobile, as shown and described.

(**) Term: **15 Years**

DESCRIPTION

(21) Appl. No.: **29/705,449**

FIG. 1 is a front elevational view of a rear combination lamp for an automobile in accordance with a first embodiment of my new design;

(22) Filed: **Sep. 12, 2019**

FIG. 2 is a rear elevational view thereof;

(30) **Foreign Application Priority Data**

Mar. 13, 2019 (JP) 2019-005217

FIG. 3 is a top plan view thereof;

(51) **LOC (12) Cl.** **26-06**

FIG. 4 is a bottom plan view thereof;

(52) **U.S. Cl.**

USPC **D26/28**

FIG. 5 is a left side elevational view thereof;

(58) **Field of Classification Search**

USPC D26/28–36, 139

CPC F21S 48/00; F21S 48/10; F21S 48/115;

F21S 48/225; F21S 48/1233; F21S

48/1266; F21S 48/1388; F21S 48/2268;

F21V 21/04; F21V 29/004; B60Q 9/13;

B60Q 9/135; B60Q 9/1375

See application file for complete search history.

FIG. 6 is a right side elevational view thereof; and,

FIG. 7 is a front side perspective view thereof.

The rear combination lamp is configured to be mounted to an automobile. The mounting structure and support structure of the rear combination lamp, shown in broken lines in FIGS. 1 to 4, 6 and 7, form no part of the claimed design since the mounting structure and support structure are hidden when the rear combination lamp is mounted to the automobile.

In addition, the appearance of the rear side structures of the rear combination lamp as shown in broken lines in FIGS. 2 to 4 and 6 is for purpose of illustrating the boundaries of the exterior surface of the rear combination lamp, and forms no part of the claimed design. The rear combination lamp has a front lens that is transparent such that features behind the lens are at least partially visible as illustrated.

A second embodiment of my new design includes the mirror image of the rear combination lamp shown in FIGS. 1 to 7.

(56) **References Cited**


U.S. PATENT DOCUMENTS

D526,427 S * 8/2006 Morioka D26/28

D550,380 S * 9/2007 Lin D26/28

D561,357 S * 2/2008 Leclercq D26/28

1 Claim, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7