US00D905900S

(12) United States Design Patent

Nykolyshyn

(10) Patent No.: US D905,900 S
(45) Date of Patent: ** Dec. 22, 2020

(54) **REFLECTOR FOR PHOTOGRAPHY OR CINEMATOGRAPHY**

(71) Applicant: **Vasyl Nykolyshyn**, Ivano-Frankivsk (UA)

(72) Inventor: **Vasyl Nykolyshyn**, Ivano-Frankivsk (UA)

(**) Term: **15 Years**

(21) Appl. No.: **35/506,526**

(22) Filed: **Jan. 9, 2019**

(80) **Hague Agreement Data**

Int. Filing Date: **Jan. 9, 2019**
Int. Reg. No.: **DM/200447**
Int. Reg. Date: **Jan. 9, 2019**
Int. Reg. Pub. Date: **Apr. 5, 2019**

(51) **LOC (12) Cl.** **26-05**
(52) **U.S. Cl.**
USPC **D26/118**; D16/237
(58) **Field of Classification Search**
USPC D16/134, 136, 200, 204, 208, 213–219, D16/235, 237–250; D26/118
CPC G02B 7/04
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,867,019	A *	2/1975	Eyerman	G03B 15/06	396/4
D243,760	S *	3/1977	Devinney, Jr.	D26/63	
D342,801	S *	12/1993	Poon	D26/45	
D353,041	S *	12/1994	Stenberg	D26/38	
D393,921	S *	4/1998	Cicolello	D26/138	
D397,234	S *	8/1998	Huang	D26/63	
D428,661	S *	7/2000	Norman	D26/63	
D437,439	S *	2/2001	Tang	D26/63	
D440,348	S *	4/2001	Tai	D26/144	
D446,329	S *	8/2001	Lau	D26/63	
7,040,780	B2 *	5/2006	Diehl	F41H 13/0056	362/234
7,137,721	B1 *	11/2006	Rao	F21V 21/0824	362/371
D580,588	S *	11/2008	Lemelson	D26/138	
D623,331	S *	9/2010	Rotwitt	D26/63	
D705,480	S *	5/2014	Acampora	D26/118	
D738,023	S *	9/2015	Rosello Gratacos	D26/63	
D759,871	S *	6/2016	Consuegra	D26/63	
D767,807	S *	9/2016	Zhou	D26/65	
D771,297	S *	11/2016	Kim	D26/63	
D781,491	S *	3/2017	Waldmann	D26/107	
D804,083	S *	11/2017	Lentine	D26/118	

* cited by examiner

Primary Examiner — Holly E Thurman

(57) **CLAIM**

The ornamental design for a reflector for photography or cinematography, as shown and described.

DESCRIPTION

1. Reflector for photography or cinematography
1.1 is a front view of reflector for photography or cinematography;
1.2 is a perspective view thereof;
1.3 is a right view thereof;
1.4 is a perspective view thereof;
1.5 is a back view thereof.
The design consists of a reflecting apparatus comprising a frame with a plurality of proximal ribs attached 360 degrees around a circular central hub base; a single distal rib is attached to each proximal rib using a joint; the ribs are extendable outwardly to assume a substantially parabolic concavity; a corona-shaped canopy is stretched across the distal ribs, and the proximal ribs are uncovered by the canopy forming a hollow; a small conical reflector is attached to the central hub base using prongs.

1 Claim, 5 Drawing Sheets



FIG. 1



1.2



1.3



1.4



FIG. 5