

US00D906847S

(12) **United States Design Patent** (10) **Patent No.:** **US D906,847 S**
Wurts et al. (45) **Date of Patent:** **** Jan. 5, 2021**

(54) **BACKFLOW TESTING DEVICE**

(71) Applicant: **Arbiter Incorporated**, Camas, WA
(US)

(72) Inventors: **Mark Wurts**, Los Angeles, CA (US);
Adolfo Jose Wurts, Washougal, WA
(US); **Demian Mendez**, Camas, WA
(US)

(73) Assignee: **Arbiter Incorporated**, Camas, WA
(US)

(**) Term: **15 Years**

(21) Appl. No.: **29/688,164**

(22) Filed: **Apr. 18, 2019**

(51) **LOC (13) Cl.** **10-04**

(52) **U.S. Cl.**
USPC **D10/96**

(58) **Field of Classification Search**
USPC D10/96, 101

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,257,208 A * 10/1993 Brown F16K 37/0091
340/626

D478,516 S * 8/2003 Larsson D10/59
(Continued)

OTHER PUBLICATIONS

General Electric Co., DPI 705 Series—Druck Handheld Pressure
Indicators—Data Sheet, downloaded from <https://www.transcat.com/media/pdf/dpi705.pdf> on Apr. 17, 2019, pp. 1-4, Transcat, 35
Vantage Point Drive, Rochester NY 14624.

Primary Examiner — Antoine Duval Davis

(74) *Attorney, Agent, or Firm* — J. Douglas Wells;
McCoy Russell LLP


(57) **CLAIM**

The ornamental design for a backflow testing device, as
shown and described.

DESCRIPTION

FIG. 1 is a front/top/left perspective view of a first embodiment of a backflow testing device, showing our new design; FIG. 2 is a rear/bottom/right perspective view thereof; FIG. 3 is a front elevation view thereof; FIG. 4 is a left side view thereof; FIG. 5 is a right side view thereof; FIG. 6 is a top plan view thereof; FIG. 7 is a bottom plan view thereof; FIG. 8 is a rear elevation view thereof; FIG. 9 is a front/top/left perspective view a second embodiment of a backflow testing device, stippled for the color black; FIG. 10 is a rear/bottom/right perspective view thereof, stippled for the color black; FIG. 11 is a front/top/left perspective view a third embodiment of a backflow testing device, wherein the stippled areas represent a contrasted color, the contrasted color being non-black but otherwise not representing a specific color or color combination; FIG. 12 is a rear/bottom/right perspective view thereof, wherein the stippled areas represent a contrasted color, the contrasted color being non-black but otherwise not representing a specific color or color combination; FIG. 13 is a front/top/left perspective view a fourth embodiment of a backflow testing device, wherein the stippled areas represent a blue-green color; and, FIG. 14 is a rear/bottom/right perspective view thereof, wherein the stippled areas represent a blue-green color. The broken line disclosure of the hook is disposed within a circular cavity in FIGS. 2, 10, 12 and 14. The broken lines shown throughout the drawing views are for illustrative purposes only and form no part of the claimed design.

1 Claim, 12 Drawing Sheets



(58) **Field of Classification Search**

CPC G01M 99/008; F17D 5/00; F16K 37/0091

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D662,845	S	*	7/2012	Guerrero		D10/96
9,476,805	B2	*	10/2016	Doran		G01M 99/008
D802,459	S	*	11/2017	Lemke		F16K 37/0091
						D10/96

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14