US00D910087S

(12) **United States Design Patent**
Moore et al.

(10) **Patent No.: US D910,087 S**
(45) **Date of Patent: ** Feb. 9, 2021**

(54) **OPERATOR PAD FOR STAND-ON MACHINE**

(71) Applicant: **Exmark Manufacturing Company, Incorporated**, Beatrice, NE (US)

(72) Inventors: **Nickolas T. Moore**, Beatrice, NE (US); **Christian Stanton Carver Bryant**, Lincoln, NE (US)

(73) Assignee: **Exmark Manufacturing Company, Incorporated**, Beatrice, NE (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/689,813**

(22) Filed: **May 2, 2019**

(51) **LOC (13) Cl.** **15-03**

(52) **U.S. Cl.**
USPC **D15/28**

(58) **Field of Classification Search**
USPC D15/28, 22–26, 14–18, 31, 33; D12/181, D12/184, 196; 296/198; 280/160, 847, 280/154, 854; 180/68.1, 900, 69.21, 180/69.22, 69.23, 69.24, 69.25, 89.1, 180/69.2, 89.12, 89.19, 273, 68.6; 56/16.1, 13.3, 15.9, 16.7, 17.4, 202, 255, 56/320.1, 13.4, 15.8, 294, 320.2
CPC .. B62D 25/161; B62D 25/168; B62D 25/182; B62D 25/18; B62D 25/16; Y10S 56/22; B60N 2/38; A01D 34/82; A01D 34/00; A01D 34/63; A01D 34/64; A01D 34/74; A01D 2101/00
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D359,740	S	*	6/1995	Crosby	D15/15
5,533,676	A	*	7/1996	Conley	A01D 43/14 239/168
D380,219	S		6/1997	Kinnard	
D380,761	S	*	7/1997	Saylor	D15/15
5,778,648	A	*	7/1998	Parkes	A01D 43/077 56/13.3
5,816,033	A	*	10/1998	Busboom	A01D 34/74 56/10.8
D409,208	S	*	5/1999	Eavenson	D15/15

(Continued)

FOREIGN PATENT DOCUMENTS

WO	2017214467	12/2017

OTHER PUBLICATIONS

"Scag V-Ride Operator's Manual," Selected pages SCAG Power Equipment 2015 (12 pages).

Primary Examiner — Mark A Goodwin
(74) *Attorney, Agent, or Firm* — Pauly, DeVries Smith & Deffner LLC

(57) **CLAIM**

The ornamental design for an operator pad for a stand-on machine, as shown and described.

DESCRIPTION

FIG. **1** is a front perspective view of an operator pad in the environment of a stand-on machine.
FIG. **2** is a perspective view of the operator pad.
FIG. **3** is a front view of the operator pad.
FIG. **4** is a right side view of the operator pad. The left side view of the operator pad is a mirror image of the right side view.
FIG. **5** is a top view of the operator pad; and,
FIG. **6** is a bottom view of the operator pad.
The broken line showing of a stand on-machine in FIG. **1** is included for the purpose of illustrating environmental structure only and forms no part of the claimed design. The broken line showing in FIGS. **1-6** of surface features of the operator pad for stand-on machine forms no part of the claimed design. The long dash short dash broken lines in the figures represents the boundaries of the claim and form no part of the claimed design.

1 Claim, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D410,931	S *	6/1999	Allen	D15/31
6,948,739	B2	9/2005	Gallagher et al.	
D588,613	S *	3/2009	Schroeder	D15/17
D624,562	S *	9/2010	Neeley	D15/17
7,793,979	B2	9/2010	Kraimer et al.	
D626,572	S *	11/2010	Moriguchi	D15/15
D655,316	S *	3/2012	Moriguchi	D15/15
8,262,104	B2	9/2012	Kallevig et al.	
D670,746	S *	11/2012	Ewringmann	D15/31
D674,816	S *	1/2013	Higashikawa	D15/15
D681,685	S *	5/2013	Higashikawa	D15/15
D715,329	S *	10/2014	Higashikawa	D15/15
D720,515	S	12/2014	Warner et al.	
8,905,183	B2	12/2014	Warner et al.	
D722,619	S *	2/2015	Phillips	D15/17
D722,620	S *	2/2015	Phillips	D15/17
D742,931	S *	11/2015	Burns, Jr.	D15/17
D751,611	S *	3/2016	Smith	D15/31
D772,309	S *	11/2016	Underhill	D15/31
D778,961	S	2/2017	Foster	
D784,426	S *	4/2017	Okuyama	D15/31
D789,423	S *	6/2017	Shi	D15/15
D806,761	S *	1/2018	Jackson	D15/31
D806,762	S *	1/2018	Loew	D15/31
D835,685	S *	12/2018	Niclot	D15/31
D866,609	S *	11/2019	Long	D15/15
D866,610	S *	11/2019	Long	D15/15
D866,611	S *	11/2019	Long	D15/15
D866,612	S *	11/2019	Long	D15/15
D896,848	S	9/2020	Moore et al.	
D897,375	S	9/2020	Moore et al.	
2005/0016782	A1	1/2005	Gallagher et al.	
2010/0289233	A1	11/2010	Kallevig et al.	

* cited by examiner



FIG. 1



FIG. 2



FIG. 4



FIG. 3



FIG. 5



FIG. 6