



US00D910188S

(12) **United States Design Patent**  
Murray et al.(10) **Patent No.:** US D910,188 S  
(45) **Date of Patent:** \*\* Feb. 9, 2021(54) **ULTRASONIC TRANSDUCER SUPPORT**(71) Applicant: **Rubicon Research Pty Ltd**, Hawthorn East (AU)(72) Inventors: **Peter Murray**, Emerald (AU); **Marius Catalin Catrina**, Southbank (AU); **David John Aughton**, Hawthorn East (AU)(73) Assignee: **RUBICON RESEARCH PTY LTD**, Hawthorn East (AU)(\*\*) Term: **15 Years**(21) Appl. No.: **29/659,557**(22) Filed: **Aug. 9, 2018**(30) **Foreign Application Priority Data**Feb. 9, 2018 (AU) ..... 201810800  
Feb. 9, 2018 (AU) ..... 201810801(51) LOC (13) Cl. ..... **24-02**

(52) U.S. Cl.

USPC ..... **D24/187**(58) **Field of Classification Search**USPC ..... D24/133, 137, 138, 141, 158, 160, 164,  
D24/165, 167, 170, 186, 187, 200;

D10/57, 60, 78, 80

CPC .... A61B 5/0095; A61B 8/4444; G01S 7/5208  
See application file for complete search history.(56) **References Cited**

## U.S. PATENT DOCUMENTS

D240,276 S \* 6/1976 Cartnell et al. ..... D24/187  
D609,812 S \* 2/2010 Shibata ..... D24/165  
D651,716 S \* 1/2012 Shibata ..... D24/165  
D654,592 S \* 2/2012 Kawasaki ..... D24/165D693,927 S \* 11/2013 Wilson ..... D24/167  
D700,341 S \* 2/2014 Uozumi ..... D24/165  
D738,233 S \* 9/2015 Repp ..... D10/57  
D740,930 S \* 10/2015 Pipe ..... D24/108  
D746,468 S \* 12/2015 Meadows ..... D24/106  
D753,311 S \* 4/2016 Long ..... D24/186  
D777,924 S \* 1/2017 Ogihara ..... D24/165  
D794,198 S \* 8/2017 Mizumura ..... D24/158  
D835,272 S \* 12/2018 Heni ..... D24/138  
D847,955 S \* 5/2019 Daniels ..... D23/262  
D850,622 S \* 6/2019 Noguchi ..... D24/165

\* cited by examiner

*Primary Examiner* — Susan Bennett Hattan*Assistant Examiner* — Omeed Agilee(74) *Attorney, Agent, or Firm* — Steven M. Koehler;  
Westman, Champlin & Koehler, P.A.

(57)

**CLAIM**

The ornamental design for an ultrasonic transducer support, as shown and described.

**DESCRIPTION**

FIG. 1 is a front perspective view of an embodiment of an ultrasonic transducer support.

FIG. 2 is a top view of the embodiment of FIG. 1;

FIG. 3 is a front view of the embodiment of FIG. 1;

FIG. 4 is a rear view of the embodiment of FIG. 1;

FIG. 5 is a left side view of the embodiment of FIG. 1;

FIG. 6 is a right side view of the embodiment of FIG. 1;

FIG. 7 is a front perspective view of a second embodiment of an ultrasonic transducer support.


FIG. 8 is a top view of the embodiment of FIG. 7;


FIG. 9 is a front view of the embodiment of FIG. 7;

FIG. 10 is a rear view of the embodiment of FIG. 7;


FIG. 11 is a left side view of the embodiment of FIG. 7; and,

FIG. 12 is a right side view of the embodiment of FIG. 7.


**1 Claim, 8 Drawing Sheets**




**FIG. 1**




**FIG. 2**




**FIG. 3**




**FIG. 4**



**FIG. 5**




**FIG. 6**




**FIG. 7**




**FIG. 8**




**FIG. 9**



**FIG. 10**



**FIG. 11**



**FIG. 12**