



US00D910638S

(12) **United States Design Patent**  
**Kuo**

(10) **Patent No.:** **US D910,638 S**

(45) **Date of Patent:** **\*\* Feb. 16, 2021**

(54) **BUCKLE**

(71) Applicant: **Getac Technology Corporation,**  
Hsinchu County (TW)

(72) Inventor: **Hsiu-Yu Kuo,** Taipei (TW)

(73) Assignee: **GETAC TECHNOLOGY CORPORATION,** Hsinchu County (TW)

(\*\*) Term: **15 Years**

(21) Appl. No.: **29/682,223**

(22) Filed: **Mar. 4, 2019**

(51) **LOC (13) Cl.** ..... **14-02**

(52) **U.S. Cl.**  
USPC ..... **D14/439; D8/349**

(58) **Field of Classification Search**  
USPC ..... D11/200, 201, 206, 212, 215, 216, 218,  
D11/220, 87; D29/100-101.5; D3/216;  
D2/627-640; D6/333; D14/447, 439,  
D14/432, 433, 434, 451, 453, 426, 440;  
D8/382, 383, 394, 395, 398, 44, 71, 72,  
D8/74, 349, 356

CPC ... A44B 11/001; A44B 11/005; A44B 11/008;  
A44B 11/02; A44B 11/00; A44B 11/065;  
A44B 11/08; A44B 11/10; A44B 11/12;  
A44B 11/125; A44B 11/14; A44B 11/226;  
A44B 11/25; A44B 11/2503; A44B  
11/2507; A44B 11/2511; A44B 11/2515;  
A44B 11/2519; A44B 11/2523; A44B  
11/253; A44B 11/2538; A44B 11/2549;  
A44B 11/2553; A44B 11/2557; A44B  
11/2561; A44B 11/2569; A44B 11/2576;  
A44B 11/258; A44B 11/2588; A44B  
11/26

See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2,266,181 A \* 12/1941 Epps ..... B65D 71/04  
206/544  
D317,760 S \* 6/1991 Esslinger ..... D14/451

D363,927 S \* 11/1995 Rosen ..... D14/451  
D469,337 S \* 1/2003 Chen ..... D8/349  
D557,897 S \* 12/2007 Richardson ..... D3/294  
D623,652 S \* 9/2010 Hsu ..... D14/439  
D624,069 S \* 9/2010 Peng ..... D14/324  
D695,748 S \* 12/2013 Morris ..... D14/447  
D771,635 S \* 11/2016 Kuo ..... D14/457

(Continued)

**FOREIGN PATENT DOCUMENTS**

EM 006222113-0001 \* 2/2019

*Primary Examiner* — Michelle E. Wilson

*Assistant Examiner* — Tracey J Bell

(74) *Attorney, Agent, or Firm* — Locke Lord LLP; Tim  
Tingkang Xia, Esq.

(57) **CLAIM**


The ornamental design for a buckle, as shown and described.

**DESCRIPTION**

FIG. 1 is a perspective view of a buckle showing the claimed design and showing the claimed design in a usage state; FIG. 2 is another perspective view thereof; FIG. 3 is a front view thereof; FIG. 4 is a rear view thereof; FIG. 5 is a left side view thereof; FIG. 6 is a right side view thereof; FIG. 7 is a top view thereof; FIG. 8 is a bottom view thereof; and, FIG. 9 is another perspective view showing the buckle being in another usage state.

The broken lines are directed to environment and are for illustrative purpose only; the broken lines form no part of the claimed design.

**1 Claim, 9 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

|              |        |                |         |
|--------------|--------|----------------|---------|
| D788,781 S * | 6/2017 | Chen .....     | D14/447 |
| D807,371 S * | 1/2018 | Bertelle ..... | D14/447 |
| D810,555 S * | 2/2018 | O'Brien .....  | D8/394  |
| D826,023 S * | 8/2018 | Chun .....     | D8/72   |
| D875,513 S * | 2/2020 | Fisher .....   | D8/383  |
| D886,107 S * | 6/2020 | Kuo .....      | D14/434 |

\* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6






FIG. 7




FIG. 8




FIG. 9