

US00D910727S

(12)

United States Design Patent
Tafe et al.

(10)

Patent No.: US D910,727 S

(45)

Date of Patent: ** Feb. 16, 2021

(54) **CATCH CAN FOR AUTOMOTIVE APPLICATIONS**

(71) Applicant: **Resource International Inc.**, New Castle, DE (US)

(72) Inventors: **Dan Tafe**, Newark, DE (US); **Kevin McCardle**, Philadelphia, PA (US)

(73) Assignee: **Resource International Inc.**, New Castle, DE (US)

(**) Term: **15 Years**

(21) Appl. No.: **29/720,199**

(22) Filed: **Jan. 10, 2020**

(51) **LOC (13) Cl.** **15-09**

(52) **U.S. Cl.**
USPC **D15/150**

(58) **Field of Classification Search**
USPC D15/150, 151, 152; D23/209, 211
CPC F01M 9/00; F01M 9/06; F01M 9/002
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,506,028 A * 8/1924 Perritt F16N 31/002
184/1.5
1,990,524 A * 2/1935 Bystricky F16N 5/00
138/34
D129,867 S * 10/1941 Dunmire D15/150
D145,692 S * 10/1946 Fitzpatrick D15/151
D232,976 S * 9/1974 Ruter D15/5
D264,614 S * 5/1982 Johnson, Sr. D23/209
D280,757 S * 9/1985 Paulovich D23/207
4,702,290 A * 10/1987 Perez B67D 7/00
141/332
4,775,067 A * 10/1988 Mount B65D 25/00
137/312
D307,913 S * 5/1990 Ogasawara D15/150

D309,974 S * 8/1990 Tannous D23/209
D311,239 S * 10/1990 Lundquist D23/209
D317,315 S * 6/1991 Miyake D15/150
D332,300 S * 1/1993 Eastom D23/211.2
D337,594 S * 7/1993 Strauch D15/152
D337,774 S * 7/1993 Schillinger D15/150
5,486,290 A * 1/1996 McGinness B01D 29/072
210/323.2
D374,447 S * 10/1996 Brewer D15/150
D379,097 S * 5/1997 Brewer D15/150
5,634,502 A * 6/1997 Pierce F01M 11/04
141/331
D396,868 S * 8/1998 Pingel D15/151
D422,914 S * 4/2000 Lasky D9/451
D438,932 S * 3/2001 McKinney D23/207
D460,146 S * 7/2002 Setser D23/209
D510,587 S * 10/2005 Tigerholm D15/150
D518,555 S * 4/2006 De Muro, Jr. D23/209
D539,822 S * 4/2007 Tseng D15/150

(Continued)

Primary Examiner — Patricia A Palasik
(74) Attorney, Agent, or Firm — Dunlap Bennett & Ludwig, PLLC; Brendan E. Squire


(57) **CLAIM**

The ornamental design for a catch can for automotive applications, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of a catch can showing our new design;
FIG. 2 is a front elevation view thereof;
FIG. 3 is a rear elevation view thereof;
FIG. 4 is a right side elevation view thereof;
FIG. 5 is a left side elevation view thereof;
FIG. 6 is a top plan view thereof; and,
FIG. 7 is a bottom plan view thereof.
The broken lines shown in the drawings illustrate portions of the catch can that form no part of the claimed design.

1 Claim, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

D562,429	S	*	2/2008	Morris		B01D 27/06
						D23/209
D621,001	S	*	8/2010	Maziel		D23/209
D638,042	S	*	5/2011	Liao		D15/152
D650,402	S	*	12/2011	Yamase		D15/150
D650,403	S	*	12/2011	Yamase		D15/150
D717,913	S	*	11/2014	Lin		D15/152
D727,462	S	*	4/2015	Antonucci		D23/209
D728,069	S	*	4/2015	Moore		D23/209
D817,440	S	*	5/2018	Lossie		D23/209
D823,916	S	*	7/2018	Lee		D15/150
D831,428	S	*	10/2018	Gibson		D7/533

* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7