



US00D912850S

(12) **United States Design Patent** (10) **Patent No.:** **US D912,850 S**
Carlson et al. (45) **Date of Patent:** **** Mar. 9, 2021**

(54) **BOLLARD**
(71) Applicant: **ABL IP Holding LLC**, Atlanta, GA (US)
(72) Inventors: **Brett S. Carlson**, Atlanta, GA (US);
Jon Eric Gibson, Covington, GA (US)
(73) Assignee: **ABL IP Holding LLC**, Atlanta, GA (US)

D708,536 S * 7/2014 Lyhne D10/113.2
D710,563 S * 8/2014 Panzer D34/35
D769,468 S * 10/2016 Pope D25/128
D769,469 S * 10/2016 Pope D25/128
D772,436 S * 11/2016 Pope D25/128
D779,085 S * 2/2017 Stern D25/126
D794,834 S * 8/2017 Edwards D25/126
D814,065 S * 3/2018 Beron D25/126
D841,879 S * 2/2019 Hollinger D26/142
D864,452 S * 10/2019 Wei D26/67
10,619,810 B1 * 4/2020 Hwang F21V 21/02

(**) Term: **15 Years**

(21) Appl. No.: **29/682,833**

(22) Filed: **Mar. 8, 2019**

(51) **LOC (13) Cl.** **25-01**

(52) **U.S. Cl.**
USPC **D25/126; D26/67**

(58) **Field of Classification Search**
USPC D10/109.1, 113.2; D25/126, 128, 129;
D26/67-71, 85, 92, 104
CPC . E01F 15/00; E01F 13/04; E01F 9/629; F21S
8/00; F21S 8/08; F21S 8/083
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D398,412 S * 9/1998 Metchear, III D26/68
D438,999 S * 3/2001 Bossy D26/68
D443,094 S * 5/2001 Landefeld D26/68
D485,374 S * 1/2004 McCue D25/126
RE40,934 E * 10/2009 Ruud F21S 8/083
362/153.1
D637,933 S * 5/2011 Macey D10/109.1
D652,976 S * 1/2012 Soto D26/68
D652,977 S * 1/2012 Soto D26/68
D675,766 S * 2/2013 Guercio D26/68
D675,767 S * 2/2013 Guercio D26/68
D678,554 S * 3/2013 Tidemann D25/126

OTHER PUBLICATIONS

signature_uk http://www.holophane.co.uk/files/listing_downloads/signature_uk-3.pdf Mar. 12, 2020 (Year: 2020).*

(Continued)

Primary Examiner — Leanne Was-Englehart

(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP


(57) **CLAIM**

The ornamental design for a bollard, as shown and described.

DESCRIPTION

FIG. 1 is an isometric view of a bollard.
FIG. 2 is a side view of the bollard of FIG. 1.
FIG. 3 is another side view of the bollard of FIG. 1.
FIG. 4 is another side view of the bollard of FIG. 1.
FIG. 5 is another side view of the bollard of FIG. 1.
FIG. 6 is a top view of the bollard of FIG. 1; and,
FIG. 7 is a bottom view of the bollard of FIG. 1.
The dash-dash broken lines depict environment that forms no part of the claimed design. The dash-dot-dash broken lines depict unclaimed boundaries of the claimed design. Contrast between components of the bollard are shown by line shading and stippling.

1 Claim, 6 Drawing Sheets



(56)

References Cited

OTHER PUBLICATIONS

PL2 Series LED Bollards, Acculite™, H7.4.6, Accessed from internet at: https://www.villalighting.com/ASSETS/DOCUMENTS/ITEMS/EN/1140483_spec%20sheet.pdf, 2015, 3 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7