



US00D916039S

(12) **United States Design Patent** (10) **Patent No.:** **US D916,039 S**
Yamanaka et al. (45) **Date of Patent:** **** Apr. 13, 2021**

(54) **SEMICONDUCTOR DEVICE**

(56) **References Cited**

(71) Applicant: **Sansha Electric Manufacturing Co., Ltd.**, Osaka (JP)

U.S. PATENT DOCUMENTS

(72) Inventors: **Tomohiro Yamanaka**, Osaka (JP);
Yoichi Makimoto, Osaka (JP)

5,408,128 A * 4/1995 Furnival H01L 23/49811
 257/690
 D364,383 S * 11/1995 Yamada D13/146
 D364,384 S * 11/1995 Shimizu D13/146
 D364,385 S * 11/1995 Shimizu D13/146
 D441,726 S * 5/2001 Sofue D13/182
 D464,618 S * 10/2002 Ando D13/110
 7,425,757 B2 * 9/2008 Takubo H01L 25/072
 257/678
 8,526,199 B2 * 9/2013 Matsumoto H01L 23/3735
 361/820
 D703,625 S * 4/2014 Lim D13/182
 D704,670 S * 5/2014 Chen D13/182
 D704,671 S * 5/2014 Chen D13/182
 D710,317 S * 8/2014 Chen D13/182
 D710,318 S * 8/2014 Chen D13/182
 D710,319 S * 8/2014 Chen D13/182
 D748,595 S * 2/2016 Bertalan D13/182
 D761,746 S * 7/2016 Toyoshima D13/182

(73) Assignee: **SANSHA ELECTRIC MANUFACTURING CO., LTD.**, Osaka (JP)

(**) Term: **15 Years**

(21) Appl. No.: **29/728,654**

(22) Filed: **Mar. 20, 2020**

(51) **LOC (13) Cl.** **13-03**

Primary Examiner — Elizabeth J Oswecki

(52) **U.S. Cl.**
USPC **D13/182**

(74) *Attorney, Agent, or Firm* — Kilyk & Bowersox, P.L.L.C.

(58) **Field of Classification Search**
 USPC D13/182
 CPC H01L 21/00; H01L 21/02; H01L 21/4814;
 H01L 21/4846; H01L 21/4871; H01L
 21/67144; H01L 2224/42; H01L 2224/43;
 H01L 2224/01; H01L 2224/08055; H01L
 2224/08054; H01L 23/12; H01L 23/13;
 H01L 23/14; H01L 23/147; H01L 23/00;
 H01L 23/48; H01L 23/4926; H01L
 23/495; H01L 23/49517; H01L 23/498;
 H01L 23/49805; H01L 23/49811; H01L
 23/49861; H01L 23/49866; H01L
 23/49872; H01L 23/49575; H01L
 23/49579; H01L 2924/171; H01L
 2924/1711; H01L 2924/1715; H01L
 2924/181; H01L 2924/1811; H01L
 2924/1815; H01L 2924/19042; H01L
 2924/1905

See application file for complete search history.

(Continued)

(57) **CLAIM**

The ornamental design for a semiconductor device, as shown and described.

DESCRIPTION

FIG. 1 is a front view of a semiconductor device, showing our new design;
 FIG. 2 is a rear view thereof;
 FIG. 3 is a top view thereof;
 FIG. 4 is a bottom view thereof;
 FIG. 5 is a left-side view thereof;
 FIG. 6 is a right-side view thereof;

(Continued)




FIG. 7 is a front top perspective view thereof;
FIG. 8 is a rear top perspective view thereof; and,
FIG. 9 is a rear side perspective view thereof.

1 Claim, 9 Drawing Sheets

(56)

References Cited

U.S. PATENT DOCUMENTS

D762,185 S * 7/2016 Muehlensiep D13/182
D762,597 S * 8/2016 Bertalan D13/182
9,418,975 B1 * 8/2016 Yoneyama H01L 23/5386
D766,851 S * 9/2016 Yoneyama D13/182
D773,412 S * 12/2016 Yoneyama D13/182
9,660,356 B1 * 5/2017 Nakamura H05K 7/1432
D790,491 S * 6/2017 Hayashida D13/182
D798,832 S * 10/2017 Hayashida D13/182
D827,591 S * 9/2018 Ikeda D13/182
D884,662 S * 5/2020 Itoh D13/182
2001/0038143 A1 * 11/2001 Sonobe H01L 24/49
257/690
2004/0227231 A1 * 11/2004 Maly H01L 25/072
257/724
2008/0142948 A1 * 6/2008 Matsumoto H01R 12/52
257/690
2016/0190915 A1 * 6/2016 Horiuchi H01L 25/072
363/132
2016/0284618 A1 * 9/2016 Tsukamoto H01L 23/645

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9