



US00D924401S

(12) **United States Design Patent** (10) **Patent No.:** **US D924,401 S**
Wittke (45) **Date of Patent:** **** Jul. 6, 2021**

(54) **OBTURATOR**

- (71) Applicant: **KARL STORZ SE & Co. KG**,
Tuttlingen (DE)
- (72) Inventor: **Uwe Wittke**, Tuttlingen (DE)
- (73) Assignee: **KARL STORZ SE & Co. KG**,
Tuttlingen (DE)
- (**) Term: **15 Years**
- (21) Appl. No.: **29/762,328**
- (22) Filed: **Dec. 16, 2020**

Related U.S. Application Data

- (62) Division of application No. 29/646,713, filed on May 7, 2018, now Pat. No. Des. 918,389.

(30) **Foreign Application Priority Data**

- Nov. 6, 2017 (EM) 004495315-0001
- Nov. 6, 2017 (EM) 004495315-0002

- (51) **LOC (13) Cl.** **24-02**

- (52) **U.S. Cl.**
USPC **D24/146**

(58) **Field of Classification Search**

- USPC D24/127, 130, 133, 146, 147
- CPC A61B 18/149; A61B 2018/00196; A61B 2018/1475; A61B 18/14; A61B 18/1485; A61B 2017/00274; A61B 2018/00577; A61B 2018/00601; A61B 2018/126; A61B 2018/1407; A61B 17/32056; A61B 2017/320004; A61B 2018/1405; A61B 2018/1861

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | |
|-------------------|---------|--------------------|----------------------|
| D373,418 S * | 9/1996 | Szpak | D24/112 |
| D590,945 S * | 4/2009 | Berberich | D24/133 |
| D603,043 S * | 10/2009 | Kreidler | D24/130 |
| D620,108 S * | 7/2010 | Eitenmueller | D24/144 |
| D635,668 S * | 4/2011 | Bartlett | D24/138 |
| D800,307 S * | 10/2017 | DeNeui | D24/146 |
| D812,750 S * | 3/2018 | Yang | D24/138 |
| D820,444 S * | 6/2018 | Pansadoro | D24/133 |
| 10,092,319 B2 * | 10/2018 | Stearns | A61M 13/006 |
| D915,593 S * | 4/2021 | Alenezi | D24/152 |
| D918,389 S * | 5/2021 | Wittke | D24/146 |
| 2015/0066018 A1 * | 3/2015 | Doll | A61B 18/16 606/39 |

* cited by examiner

Primary Examiner — Samantha Q Lawrence

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **CLAIM**

The ornamental design for an obturator, as shown and described.

DESCRIPTION

FIG. 1 is a front perspective view of an obturator of the present invention.

FIG. 2 is a front view of the obturator of FIG. 1.

FIG. 3 is a rear view of the obturator of FIG. 1.


FIG. 4 is a left side view of the obturator of FIG. 1.

FIG. 5 is a right side view of the obturator of FIG. 1.

FIG. 6 is a top view of the obturator of FIG. 1; and,

FIG. 7 is a bottom view of the obturator of FIG. 1.

1 Claim, 7 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7