US00D925623S

(12) United States Design Patent

Valentini

(10) Patent No.: US D925,623 S
(45) Date of Patent: ** Jul. 20, 2021

(54) **PROTECTIVE CAP**

(71) Applicant: **Guido Valentini**, Milan (IT)

(72) Inventor: **Guido Valentini**, Milan (IT)

(**) Term: **15 Years**

(21) Appl. No.: **29/703,286**

(22) Filed: **Aug. 26, 2019**

(30) **Foreign Application Priority Data**

Feb. 28, 2019 (EM) 006270658

(51) **LOC (13) Cl.** **15-09**

(52) **U.S. Cl.**
USPC **D15/126**; D8/70

(58) **Field of Classification Search**
USPC D3/202; D7/300, 300.1, 387, 391, 392, D7/392.1, 393, 394, 396.1, 396.2, 401.1, D7/509, 510, 511, 533, 536, 543, 589, D7/591, 601, 602, 619.1; D9/434, 435, D9/436, 438, 439, 440, 441, 443, 445, D9/447, 448, 449, 454, 516, 520, 530, D9/531, 686, 730, 733; D23/206, 227, D23/249, 259, 260, 261, 313; D4/109, D4/111; D8/8, 61, 62, 70; D15/138, 139
CPC B65D 2251/1066; B65D 2251/1058; B65D 47/0819; B65D 1/00; B65D 1/02; B65D 1/0223; B65D 2203/00; B65D 2203/02; B65D 81/60; B65D 81/365; B65D 81/366; B65D 81/368; B65D 2539/008; B65D 39/0094; B65D 2543/00046; B65D 2543/00027; B65D 2543/00092; B65D 2543/00296; B65D 2543/00351; B65D 2543/00537; B65D 2543/00731; B65D 43/0212; B65D 43/0218; A01G 31/02; B02C 18/16; B02C 18/18; B02C 18/24; A47J 42/08; A47J 42/38; A47J 42/04; A47J 42/46; A47J 42/16; A47J 42/14; A47J 42/34; A47J 42/40; A47J 42/25; A47J 42/255
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

D282,340	S	*	1/1986	Lam	D7/387
D289,848	S	*	5/1987	Cowan	D7/387
D753,949	S	*	4/2016	Potter	D7/391
D804,240	S	*	12/2017	Freeman	D7/391
D818,765	S	*	5/2018	Ulanski	D7/391

(Continued)

OTHER PUBLICATIONS

IBrid Nano Sander: Announced Sep. 26, 2020 [online]. Site Visited [Apr. 2, 2021]. Available from Internet URL: https://www.rupes.com/product/ibrid-nano-sander-with-q-mag-magnetic-technology-q-mag/.*

Primary Examiner — Catherine S Posthauer
(74) *Attorney, Agent, or Firm* — Ware, Fressola, Maguire & Barber LLP

(57) **CLAIM**

The ornamental design for a protective cap, as shown and described.

DESCRIPTION

FIG. **1** shows a top perspective view of a protective cap, showing my new design;
FIG. **2** shows a front view of the protective cap, shown in FIG. **1**;
FIG. **3** shows a back view of the protective cap, shown in FIG. **1**;
FIG. **4** shows a right side view of the protective cap, shown in FIG. **1**;
FIG. **5** shows a left side view of the protective cap, shown in FIG. **1**;
FIG. **6** shows a top view of the protective cap, shown in FIG. **1**; and,
FIG. **7** shows a bottom view of the protective cap, shown in FIG. **1**.

1 Claim, 4 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

D843,165	S	*	3/2019	Chen	D7/391
D865,448	S	*	11/2019	Jacobsen	D7/511
D866,323	S	*	11/2019	Miksovsky	D9/443
D867,068	S	*	11/2019	Jacobsen	D7/511
D868,537	S	*	12/2019	Jacobsen	D7/511
D868,538	S	*	12/2019	Jacobsen	D7/511
D893,244	S	*	8/2020	Marina	D7/392.1

* cited by examiner



FIG. 1



FIG. 2



FIG. 3



FIG. 4



FIG. 5



FIG. 6



FIG. 7